

I2.0 Recommended Finishes Schedule

Amend to suit Project

EXTERNAL

Location	System	LOGICWALL® Requirements	Panel Joints	Finishing System(1)
	Marine, Coastal(2)	Refer AS3600	External Flush Set	Refer Façade Consultant
	Near Coastal (1 to 50 km)	F'c 40 Mpa minimum Central reinforcement only All external fitting, fixtures, render strips to be UPVC or Stainless.	External Flush Set	Dulux AcraTex High Build System, Duspec AC1202 Issue 4. Dulux Material Warranty (Project Specific) 10year applicable on approved systems incorporating (2) final Weatherproofing AcraShield or AcraSkin Topcoat. 10 year applicable on approved systems incorporating (1) final Weatherproofing AcraShield or AcraSkin Topcoat.
	Inland Tropical	Standard AFS LOGICWALL®	External Flush Set	DULUX Acratex - AFS LOGICWALL W&W Interior Finish System. Issue 1.1

INTERNAL

Location	System	LOGICWALL® Requirements	Panel Joints	Finishing System(1)
	DULUX Interior	Standard AFS LOGICWALL®	Internal Flush Set	DULUX Acratex - AFS LOGICWALL W&W Interior Finish System. Issue 1.1
	System 1 - Joint Setting Only	Standard AFS LOGICWALL®	Internal Flush Set	not used
	System 2 - Joint Setting and Skim Coating	Standard AFS LOGICWALL®	Internal Flush Set	Method 1 - Spray applied thin Gyprock Total Joint Cement Method 2 - Roller applied thin Gyprock Total Joint Cement
	System 3 - Over Sheeting	Standard AFS LOGICWALL®	Internal Flush Set	Method 1 - Direct Stick Plasterboard finish to Architectural Specification Method 2 - Batten and sheet finish to Architectural Specification

- (1) Refer AFS Data Manual for Details and specifications for finishes.
- (2) All external fixtures, fixings, moldings etc in Coastal or Marine Environments AS2312 Classification D or greater to be UPVC or Stainless.

Note: All external steel fixtures, fixings, mouldings to be galvanized.