

EXTERNAL

INTERNAL

EXTERNAL FINISHES TO PROJECT'S SPECIFICATION (REFER RECOMMENDED FINISHES SCHEDULE)

TWO CONTINUOUS BEADS OF SEALANT UNDER FLOOR TRACK ON ALL EXTERNAL WALLS AND INTERNAL SEPARATION WALLS

FLASHING

AFS LOGICWALL PUNCHED FLOOR TRACK

THIS HORIZONTAL JOINT CAN BE TREATED USING THE BANDING STRIP OR MEMBRANE DETAIL, AS OUTLINED IN EARLIER DETAILS - DEPENDENT ON THE NATURAL GROUND LEVEL (BY OTHERS)


EDGE BEAM AND REINFORCEMENT TO ENGINEER'S DETAILS

VERTICAL AND HORIZONTAL REINFORCEMENT TO ENGINEERS DETAILS

VOID GROUT FILLED

PAINTABLE WATERPROOFING MEMBRANE BY OTHERS
SET DOWN IN SLAB AS DETAILED BY STRUCTURAL ENGINEER

CONCRETE FLOOR SLAB TO ENGINEERS DETAILS



EXTERNAL WALL/SLAB JUNCTION FOR TYPICAL RAFT SLAB



AFS Walling Solutions
PO Box 234, Minto NSW 2566
110 Airds Road, Minto NSW 2566
Phone: 1300 727 237
Fax: 1300 715 237
Web Page: www.afswall.com.au
we put you in front

DRAWING NO

120-I2.1.9

SCALE

1:4

REV NO

A

LOGICWALL®
STRUCTURAL SOLUTION