



Contents

Introduction	4
Rediwall® Capabilities Overview.	5
Definition of Terms Used in this Section.....	6
Flexural Capacity	6
Lintels	6
Reinforcement Requirements	7
Minimum Reinforcement	7
Reinforcement Detailing Constraints.....	7
Rediwall® Design for Earthquake Actions	8
Non Ductile Wall Design	8
Axial Capacity	8
Rediwall® Structural Design Tables	9
RW110C Structural Capacities.....	9
RW156C Structural Capacities.....	11
RW156C In-plane Shear Along Vertical PVC Webs	13
RW200C Structural Capacities.....	14
RW200C In-plane Shear Along Vertical PVC Webs	16
RW200C Structural Capacities (Double Reinforcement)	17
RW200C Double Reinforcement In-plane Shear Along Vertical PVC Webs.....	19
RW256S Structural Capacities.....	20
RW256S In-plane Shear Along Vertical PVC Webs.....	22
RW275S Structural Capacities.....	23
RW275S In-plane Shear Along Vertical PVC Webs.....	25
RW300S Structural Capacities.....	26
RW300S In-plane Shear Along Vertical PVC Webs.....	28
Non-Ductile Wall Detailing	29
Junctions	29
Standard wall junctions	29
Non-Ductile Blade Walls/Columns.....	32
Joints.....	33
Limited Ductile Wall Design	34
Limited Ductile Design	34
Limited Ductile Design Examples	35
Limited Ductile Wall Detailing	37
Boundary Elements.....	37
Limited Ductile Wall Horizontal Reinforcement Wall Laps.....	39
Blade Columns	40
Junctions	40
Movement Joints	41
Construction Joint.....	42
Wall Junctions Joints	42
Temporary Works.....	42
Core Filling of Walls.	43
Introduction	43
Concrete Pour Limitations.....	43
Additional Equipment Required for Concrete Pour	43
Concrete Mix Design.....	44
Performance	45
Fire Testing	46
Fire Resistance Levels (FRL)s.....	46

Contents (continued)

Non-Combustibility – Wall Applications & Finishes.....	48
Non-Combustibility – Specific Wall Applications	54
Acoustic Performance.....	58
Thermal Insulation.....	61
Weatherproofing	63
Termite Resistance.....	63
Bushfire Resistance	63

Appendices 64

AFS Rediwall® Standard Bracing & Lifting Bar.....	64
Certifications.....	64
AFS Rediwall Standard Bracing	65
AFS Rediwall® Standard Lifting Bar.....	66
Rediwall® CodeMark Certificate of Conformity	67
AFS Rediwall® Fire Resistance Level (FRL) Reports.....	68
Stephen Grubits & Associates – Rediwall® CodeMark Evaluation	74
Rediwall® AS5113 Facade Test Report	75
Rediwall® AS5637.1 Classification Report.....	76
Rediwall® AS1530.3 Fire Hazard Properties Test Report	77
Rediwall® Acoustic Performance Assessment Reports	78
Rediwall® AS/NZS 4859 Thermal Performance Assessments	84
Rediwall® Weatherproofing Assessment Report.....	85

Introduction

Volume 1– 'AFS Rediwall® Design, Performance and Compliance Guide' forms part of a comprehensive afs rediwall® Systems Manual that encompasses Volume 1 , 2 and 3. This manual covers the aspects of Design, Performance, Compliance, Construction and Installation for all rediwall® products current at the time of publication.


Volume 1 should be read in conjunction with Volume 2 and 3. Downloads of these individual Volumes are available via the Resource Centre at www.afsformwork.com.au

Disclaimer: This section of the afs rediwall® Systems Manual is intended to represent good building practice in achieving structural design of rediwall®. This section is not intended in any way by AFS to represent all relevant information required on a project. It is the responsibility of those using and designing rediwall®, including but not limited to builders, designers, consultants and engineers to ensure that the use of rediwall® complies with all the relevant National Construction Code (NCC) requirements such as, but not limited to structural adequacy, acoustic, fire resistance/combustibility, thermal, and weatherproofing provisions. All diagrams, plans and illustrations used in this section, including any reinforcement shown, are supplied for indicative and diagrammatic purposes only. It remains the responsibility of those using rediwall® to ensure that reference is made to the project engineer's structural details for all construction and reinforcement requirements.



Rediwall® Capabilities Overview

Rediwall® System Capabilities



Note: If rediwall® is exposed to UV, appropriate protective finish shall be applied.

Definition of Terms Used in this Section

t_w	Effective structural concrete wall width
$t_{w,fire}$	Effective wall width for fire
S_{web}	Web spacing
S_{punch}	Vertical punch spacing
A_c	Percentage of web opening
Align	Allowance for on-site mis-alignment of web openings
N_{layers}	Number of Reinforcement layers
d_h	Distance to centre of horizontal bar from the rediwall® concrete face
$f'_{c,max}$	Maximum concrete strength
f_y	Steel yield stress
Bar Max	Max reinforcement bar size
e	The eccentricity of the load measured at right angle to the plane of the wall
H_{wu}	Unsupported wall height
H_{we}	Effective wall height

Flexural Capacity

The flexural strength of rediwall® s obtained by the stud flanges acting as reinforcement therefore from classic beam theory ignoring axial forces and any vertical reinforcement:

$$\phi M_u = f_{stud} t_w A_{flange} \left(1 - 0.6 \frac{A_{flange}}{b t_w} \frac{f_{stud}}{f'_c} \right)$$

Where:

- $\phi = 0.8$ strength reduction factor
- M_u ultimate flexural capacity
- f_{stud} yield strength of vertical studs
- A_{flange} area of stud flange
- f'_c characteristic compressive strength of concrete

Since the stud flanges are potentially exposed to fire they can only be used for Wind Loads in accordance with AS/NZS1170.2.

If flexural capacity other than Wind Loads is required then the wall may be reinforced and designed as a normal reinforced concrete wall.

Lintels

Lintel tables have been prepared based on a wall with minimum reinforcement for bending and shear capacity. If additional capacity is required, extra reinforcement can be designed and detailed by the engineer.

Reinforcement Requirements

The individual cells within afs rediwall® allow horizontal shrinkage and thermal movements in the concrete with the internal studs acting as crack inducers. This allows afs rediwall® to provide crack control without additional reinforcement. The vertical studs can be considered as non fire-rated vertical reinforcement.

For fire-rated reinforced walls to AS3600-2018 Cl11.7.1 use minimum vertical reinforcement ratio (p_w) of 0.0015 or the value required by structural analysis.

Due to the presence of the steel studs in afs rediwall® steel congestion should be avoided to facilitate adequate compaction of concrete. As a guide steel ratios in excess of 0.02 in a single layer should not be used unless the amount and disposition of the reinforcement will not prevent the proper placement and compaction of the concrete at splices and at junctions of members.

Minimum Reinforcement

For walls required that have tensile forces from any load combination AS3600-2018 11.7 Minimum reinforcement shall apply.

Examples of such walls are:

- Walls resisting lateral loads
- Walls acting as deep beams
- Walls with load combinations of bending and compression producing tension stress.
- Where reinforced afs rediwall® walls do not require a high degree of crack control for tensile forces we recommend a minimum reinforcement spacing of 400mm.

- Horizontal reinforcement may be reduced to zero for walls supporting vertical loads only where the wall is designed for one way buckling and the studs act as crack inducers for removing restraint against horizontal shrinkage or thermal movement.

Notes: AS3600 does not recognise the use of plain concrete in wall elements, though some International standards offer guidance in this area. Use of afs rediwall® walls unreinforced will require reference to other codes such as ACI 318 and BS8110.1 where it can be shown that no tensile forces result from any load combination of bending and compression.

TABLE A1: Minimum Reinforcement for Reinforced Walls ($p = A_{st}/A_{conc}$)

Location	Vertical (p)	Horizontal (p)
Internal (A1, A2)	0.0025 (0.0015 Cl.11.7.1(a))	0.0015
External (B1, B2)	0.0025 (0.0015 Cl.11.7.1(a))	0.0025
Limited Ductile	0.0025	0.0025
Deep Beam	AS3600 Sect 12	AS3600 Sect 12

Steel ratios in excess of 0.02 in a single layer should not be used unless the amount and disposition of the reinforcement will not prevent the proper placement of the concrete in walls and at splices and junction members.

Reinforcement Detailing Constraints

For heavily loaded walls where reinforcement ratio is high, it is critical that reinforcement is detailed carefully to avoid congestion within the wall which creates difficulties when core filling and may result in voids or insufficient concrete compaction.

When detailing reinforcement to be placed in Rediwall® the following spacing constraints must be noted:

- For single reinforcement carrier walls the reinforcement is centrally placed at minimum horizontal centres as shown.
- For double reinforcement carrier walls, RW200C

and RW256S, RW275S & RW300S the reinforcement is located toward each face of the wall with concrete cover as shown.

- Typical total reinforcement rates are less than 0.01. Rates in excess of 0.02 are not recommended as it creates possible congestion issues.
- Areas with higher reinforcement concentrations such as laps and corners should be reviewed.

Rediwall® Design for Earthquake Actions

Rediwall® is to be designed to cater for earthquake actions as per AS1170.4 Earthquake Actions and AS3600-2018 Section 14 Design for Earthquake Actions. The design and detailing of the wall will depend on the Structural System selected by the designer for

the building from Table 14.3 Structural Ductility Factor and Structural Performance Factor. This will normally be either Non-Ductile Structural Walls or Limited Ductile Structural Walls.

Non Ductile Wall Design

The use of the Simplified Design Method in Section 11.5 is limited to Non-Ductile Walls by Cl 14.4.4.1 and Cl 11.5.2 Limitations on the use of the Method. Non-Ductile Rediwall® are to designed to Section 2.2 and 14.4.

14.4.4.1 General

"Walls shall be designed in accordance with Section 10 or Section 11 as appropriate except that the simplified design method for walls subjected to vertical compression forces provided in Clause 11.5 of this standard shall only be used for non-ductile walls."


Axial Capacity

AFS Rediwall® can be designed in accordance with Section 11 of AS3600 – 2018.

$$\phi N_u = \phi (t_w - 1.2e - 2e_a) 0.6f_c \quad [\text{AS3600 Cl.11.5.3}]$$

Where:

- $\phi = 0.65$ strength reduction factor
- $N_u =$ ultimate strength per unit wall length
- $t_w =$ thickness of the wall
- $e =$ eccentricity of the load measured at right angles to the plane of the wall
- $e_a = \frac{H_{we}^2}{2500t_w}$ an additional eccentricity
- $H_{we} = kH_{wu}$ effective height of a braced wall



[AS3600 Cl.11.5.3]

11.5.2 Limitation on use of method


"Structural walls designed using Clause 11.5.3 Shall –

- (a) be limited to a maximum design axial stress of 3 MPa unless vertical and horizontal reinforcement is provided on both wall faces and divided equally between the two wall faces;
- (b) not constructed on sites with soil classifications of De or Ee, as defined in AS 1170.4, and where subjected to earthquake design actions; and
- (c) have a ratio of effective height to thickness that does not exceed 20 for singly reinforced wall or 30 for doubly reinforced walls.

Otherwise, the wall shall be designed as a column in accordance with Section 10."


Rediwall® Structural Design Tables

RW110C Structural Capacities



RW110C Axial Capacity ϕN_u (kN/m)

t_w	t_{fire}	S_{web}	S_{punch}	A_c	N_{layers}	d_h	$f'_{c,max}$
105	105	66.6	175	36.9%	1	52.5	40



k = 0.75		Continuous Floor $e = 0.05 t_w$			Discontinuous Floor $e = 1/6 t_w$		
H_{wu}	H_{we}	25 MPa	32 MPa	40 MPa	25 MPa	32 MPa	40 MPa
3000	2250	541	693	866	409	523	654
2700	2025	607	777	971	475	608	760
2400	1800	666	853	1066	534	683	854
2100	1575	718	919	1149	586	750	937
1800	1350	763	977	1221	631	808	1010
Limit with bottom plate		861	1102	1377	861	1102	1377

RW110C Minimum Reinforcement

RW110C		Vertical Bars (min. N12-350)			
Allowable Bars		N12	N16	N20	N24
Horizontal (min. N12-350)	N12				
	N16				
	N20				
	N24				

Horizontal Bar Spacing 175/350

Vertical Bar Spacing 150 to 350


Acceptable
With Caution
Not Recommended

RW110C Out of Plane Flexural Capacity (ϕM_u kNm/m) ($N^*=0$)

Vert. Bars	d	ρ	25 MPa	32 MPa	40 MPa	50 MPa
N12@400	41	0.007	–	–	–	–
N12@300	41	0.0093	5.42	–	–	–
N12@250	41	0.0112	6.34	6.56	–	–
N16@400	39	0.0131	6.53	6.79	6.98	7.13
N16@350	39	0.0149	7.26	7.61	7.85	8.05
N16@300	39	0.0174	8.16	8.63	8.97	9.24
N16@250	39	0.0209	9.28	9.96	10.44	10.83
N16@200	39	0.0261	10.63	11.69	12.45	13.05
$\rho_{st,min}$ [8.1.6.1.(2)]			0.0089	0.0101	0.0113	0.0126
$\phi M_u = \phi(f_y \rho b d^2 (1 - 0.6 \rho f_y / f_c))$						

RW110C Standard Lintels with Vertical PVC Webs

UDL capacity of a simple standard lintel with minimum reinforcement other than extra top and bottom bars shown. Designer can utilise the slab over as T-beam, extra horizontal or vertical shear reinforcement if extra strength is required.



1N12 OR 1N16
Top & Bottom

Section

$$M_u = \left[f_y \cdot p \cdot t_w \cdot d_0^2 \cdot \left\{ 1 - 0.6 p \cdot \frac{f_y}{f_c} \right\} \right]$$


$$V_{uc} = K_y \cdot (A_c \cdot t_w) \cdot d_0 \cdot \sqrt{f_c}$$

RW110C Standard Lintels with Vertical PVC Webs w^* (kN/m) UDL

D	1N12 Top & Bottom, Depth (mm)				1N16 Top & Bottom, Depth (mm)			
	150	300	450	750	150	300	450	750
Span (mm)								
3600	4.7	9.8	14.9	25.1	5.6	10.8	16.2	28.8
3300	5.5	11.6	17.7	29.8	5.1	12.1	18.2	33.6
3000	6.7	13.6	20.8	36.1	6.8	13.6	20.8	40.3
2700	7.7	15.5	24.3		7.7	15.5	24.3	
2400	8.8	18.1	29.2		8.8	18.1	29.2	
2100	10.2	21.7	36.5		10.2	21.7	36.5	
1800	12.3	27.1			12.3	27.1		
1500	15.3	36.2			15.3	36.2		
1200	20.4				20.4			
900	30.7				30.7			


 = ϕV_{uc} governs, otherwise ϕM_u
 = Design to AS3600–2018 Sect 12

RW156C Structural Capacities



RW156C Axial Capacity ϕN_u (kN/m)

t_w	t_{fire}	S_{web}	S_{punch}	A_c	N_{layers}	d_h	$f'_{c,max}$
151	151	66.6	175	44.3%	1	75.5	50



$k = 0.75$		Continuous Floor $e = 0.05 t_w$				Discontinuous Floor $e = 1/6 t_w$			
H_{wu}	H_{we}	25 MPa	32 MPa	40 MPa	50 MPa	25 MPa	32 MPa	40 MPa	50 MPa
3900	2925	870	1113	1391	1739	679	869	1087	1358
3600	2700	930	1190	1488	1860	740	947	1183	1479
3300	2475	985	1261	1577	1971	795	1018	1272	1590
3000	2250	1036	1326	1658	2072	846	1083	1353	1692
2700	2025	1082	1385	1731	2164	892	1141	1427	1783
2400	1800	1123	1437	1797	2246	933	1194	1492	1865
2100	1575	1159	1484	1855	2318	969	1240	1550	1938
1800	1350	1191	1524	1905	2381	1000	1280	1600	2001
Limit with bottom plate		1357	1737	2171	2713	1357	1737	2171	2713

RW156C Minimum Reinforcement

RW156C		Vertical Bars (min. N12-300)			
Allowable Bars		N12	N16	N20	N24
Horizontal (min. N12-350)	N12	Acceptable	Acceptable	Acceptable	Not Recommended
	N16	Acceptable	With Caution	Not Recommended	Not Recommended
	N20	Not Recommended	Not Recommended	Not Recommended	Not Recommended
	N24	Not Recommended	Not Recommended	Not Recommended	Not Recommended

Horizontal Bar Spacing 175/350
Vertical Bar Spacing 150 to 350

Acceptable

With Caution


Not Recommended

RW156C Out of Plane Flexural Capacity ϕM_u (kNm/m) ($N^*=0$)

Vert. Bars	d	ρ	25 MPa	32 MPa	40 MPa	50 MPa
N16@400	62	0.0082	11.15	–	–	–
N16@350	62	0.0093	12.54	12.89	–	–
N16@300	62	0.0109	14.33	14.8	15.14	–
N16@250	62	0.0131	16.68	17.35	17.84	18.23
N16@200	62	0.0163	19.87	20.94	21.69	22.3
N20@300	60	0.0176	19.65	20.8	21.62	22.28
N20@250	60	0.0211	22.32	23.98	25.16	26.11
N20@200	60	0.0264	25.53	28.12	29.97	31.45
$\rho_{st,min}$ [8.1.6.1.(2)]			0.0077	0.0087	0.0098	0.0109
$\phi M_u = \phi(f_y \rho b d^2 (1 - 0.6 \rho f_y / f'_c))$						

RW156C Standard Lintels with Vertical PVC Webs

UDL capacity of a simple standard lintel with minimum reinforcement other than extra top and bottom bars shown. Designer can utilise the slab over as T-beam, extra horizontal or vertical shear reinforcement if extra strength is required.



RW156C Standard Lintels with Vertical PVC Webs w^* (kN/m) UDL

D	1N12 Top & Bottom, Depth (mm)				1N16 Top & Bottom, Depth (mm)			
	150	300	450	750	150	300	450	750
Span (mm)								
3600	4.8	9.9	15.0	25.2	8.1	17.1	26.1	44.2
3300	5.7	11.8	17.8	30.0	9.6	20.3	31.1	52.6
3000	6.9	14.2	21.6	36.3	11.6	23.3	35.7	63.6
2700	8.5	17.6	26.7		13.1	26.6	41.7	
2400	10.8	22.3	33.7		15.0	31.0	50.0	
2100	14.1	29.1	44.1		17.5	37.2	62.6	
1800	19.2	39.6			21.0	46.5		
1500	26.3	57.0			26.3	62.0		
1200	35.1				35.1			
900	52.6				52.6			

 = ϕV_{uc} governs, otherwise ϕM_u
 = Design to AS3600–2018 Sect 12

RW156C In-plane Shear Along Vertical PVC Webs


RW156C PVC Profile/Spacing

t_w	S_{punch}	N_{layers}	A_c	Align	Bar Max	Min Reo	Max Spacing	$t_{w,\text{shear}}$	μ	k_{co}
151	175	1	44.3%	80%	20	0.0025	350	53.5	0.32	0.18

RW156C In Plane Shear along Vertical PVC Web ϕV_u (kN/m)


Horizontal Bars	ρ	25 MPa	32 MPa	40 MPa	50 MPa
N12@263*	0.0028	81.7	86.1	90.6	95.6
N16@350	0.0038	97.8	102.2	106.7	111.8
N12@175	0.0043	105.8	110.2	114.7	119.8
N16@175	0.0076	161.9	166.3	170.8	175.9
Max. Shear		187.3	239.7	299.6	374.6
$\phi V_u = \phi(\mu \rho t_w f_y + k_{co} t_w f'_{ct})$					
$\phi V_{\text{max}} = \phi 0.2 f'_c t_{w \text{ shear}} < \phi 10 t_{w \text{ shear}}$					
* 263 spacing, 2 bars every three web punches.					

RW200C Structural Capacities



RW200C Axial Capacity ϕN_u (kN/m)

t_w	t_{fire}	S_{web}	S_{punch}	A_c	N_{layers}	d_h	$f'_{c,max}$
195	195	66.6	116.7	50.1%	1	97.5	65



$k = 0.75$		Continuous Floor $e = 0.05 t_w$					Discontinuous Floor $e = 1/6 t_w$				
H_{wu}	H_{we}	25 MPa	32 MPa	40 MPa	50 MPa	65 MPa*	25 MPa	32 MPa	40 MPa	50 MPa	65 MPa*
5000	3750	1130	1447	1809	2261	2939	885	1133	1416	1770	2300
4500	3375	1229	1573	1967	2458	3196	983	1259	1573	1967	2557
4200	3150	1283	1643	2053	2567	3337	1038	1328	1660	2075	2698
3900	2925	1334	1707	2134	2668	3468	1088	1393	1741	2176	2829
3600	2700	1381	1767	2209	2761	3589	1135	1453	1816	2270	2951
3300	2475	1424	1822	2278	2847	3701	1178	1508	1885	2356	3062
3000	2250	1463	1872	2340	2926	3803	1217	1558	1947	2434	3164
2700	2025	1498	1918	2397	2997	3896	1253	1603	2004	2505	3257
2400	1800	1530	1958	2448	3060	3978	1284	1644	2055	2569	3339
2100	1575	1558	1994	2493	3116	4051	1312	1680	2100	2625	3412
1800	1350	1582	2025	2532	3165	4114	1337	1711	2139	2673	3475
Limit with bottom plate		1863	2385	2982	3727	4845	1863	2385	2982	3727	4845

* for $f'_c > 50$ MPa, CSR appointed installer only.

RW200C Minimum Reinforcement

RW200C		Vertical Bars (min. N12-350)			
Allowable Bars		N12	N16	N20	N24
Horizontal (min. N12-350)	N12				
	N16				
	N20				
	N24				

Horizontal Bar Spacing 233/350
Vertical Bar Spacing 150 to 350

Acceptable
With Caution
Not Recommended


RW200C Out of Plane Flexural Capacity (ϕM_u kNm/m) ($N^*=0$)

Vertical Bars	d	ρ	25 MPa	32 MPa	40 MPa	50 MPa	65 MPa
N16@350	84	0.0069	17.6	–	–	–	–
N16@300	84	0.008	20.22	20.69	–	–	–
N16@250	84	0.0096	23.75	24.43	24.91	–	–
N16@200	84	0.012	28.72	29.78	30.54	31.14	31.7
N20@300	82	0.0128	28.86	30.01	30.83	31.49	32.1
N20@250	82	0.0154	33.37	35.03	36.21	37.16	38.03
N20@200	82	0.0193	39.35	41.94	43.79	45.27	46.63
$\rho_{st,min}$ [8.1.6.1.(2)]			0.0069	0.0078	0.0087	0.0097	0.0111

$\phi M_u = \phi(f_y \rho b d^2 (1 - 0.6 \rho f_y / f'_c))$

RW200C Standard Lintels with Vertical PVC Webs

UDL capacity of a simple standard lintel with minimum reinforcement other than extra top and bottom bars shown. Designer can utilise the slab over as T-beam, extra horizontal or vertical shear reinforcement if extra strength is required.



RW200C Standard Lintels with Vertical PVC Webs w^* (kN/m)

D	2N12 Top & Bottom, Depth (mm)				2N16 Top & Bottom, Depth (mm)			
	150	300	450	750	150	300	450	750
Span (mm)								
3600	4.9	10.0	15.1	25.3	8.3	17.3	26.3	44.4
3300	5.8	11.9	17.9	30.1	9.9	20.6	31.3	52.8
3000	7.0	14.3	21.7	36.4	11.9	24.9	37.9	63.9
2700	8.6	17.7	26.8		14.7	30.8	46.8	
2400	10.9	22.4	33.9		18.6	39.0	59.3	
2100	14.3	29.3	44.3		24.4	50.9	77.4	
1800	19.5	39.9			30.9	68.4		
1500	28.0	57.4			38.7	91.2		
1200	43.8				51.5			
900	77.3				77.3			

 = ϕV_{uc} governs, otherwise ϕM_u
 = Design to AS3600–2018 Sect 12

RW200C In-plane Shear Along Vertical PVC Webs


RW200C PVC Profile/Spacing

t_w	S_{punch}	N_{layers}	A_c	Align	Bar Max	Min Reo	Max Spacing	$t_{w,\text{shear}}$	μ	k_{co}
195	117	1	50.1%	80%	20	0.0025	350	78.2	0.36	0.20

RW200C In Plane Shear along Vertical PVC Web ϕV_u (kN/m)


Horizontal Bars	ρ	25 MPa	32 MPa	40 MPa	50 MPa	65 MPa
N12@233	0.0025	110.5	117	123.5	130.9	140.6
N16@350	0.0029	121.8	128.2	134.8	142.2	151.9
N16@233	0.0044	158.2	164.6	171.2	178.6	188.3
N20@350	0.0046	162.5	169	175.6	182.9	192.7
N20@233	0.0069	219.4	225.9	232.5	239.8	249.6
N16@117	0.0088	266.2	272.6	279.2	286.6	296.3
Max. Shear		273.6	350.2	437.7	547.2	547.2
$\phi V_u = \phi(\mu \rho t_w f_y + k_{co} t_w f'_{ct})$						
$\phi V_{\text{max}} = \phi 0.2 f'_c t_w \text{ shear} < \phi 10 t_w \text{ shear}$						

RW200C Structural Capacities (Double Reinforcement)



RW200C Double Reinforcement Axial Capacity ϕN_u (kN/m)

t_w	t_{fire}	S_{web}	S_{punch}	A_c	N_{layers}	d_h	$f'_{c,max}$
195	195	66.6	116.7	50.1%	2	38.5	65



k = 0.75		Continuous Floor e = 0.05t _w					Discontinuous Floor e = 1/6t _w				
H _{wu}	H _{we}	25 MPa	32 MPa	40 MPa	50 MPa	65 MPa*#	25 MPa	32 MPa	40 MPa	50 MPa	65 MPa*#
6000	4500	902	1155	1443	1804	2345	656	840	1050	1313	1706
5000	3750	1130	1447	1809	2261	2939	885	1133	1416	1770	2300
4500	3375	1229	1573	1967	2458	3196	983	1259	1573	1967	2557
4200	3150	1283	1643	2053	2567	3337	1038	1328	1660	2075	2698
3900	2925	1334	1707	2134	2668	3468	1088	1393	1741	2176	2829
3600	2700	1381	1767	2209	2761	3589	1135	1453	1816	2270	2951
3300	2475	1424	1822	2278	2847	3701	1178	1508	1885	2356	3062
3000	2250	1463	1872	2340	2926	3803	1217	1558	1947	2434	3164
2700	2025	1498	1918	2397	2997	3896	1253	1603	2004	2505	3257
2400	1800	1530	1958	2448	3060	3978	1284	1644	2055	2569	3339
2100	1575	1558	1994	2493	3116	4051	1312	1680	2100	2625	3412
1800	1350	1582	2025	2532	3165	4114	1337	1711	2139	2673	3475
Limit with bottom plate		1863	2385	2982	3727	4845	1863	2385	2982	3727	4845

* for $f'_c > 50$ MPa, CSR appointed installer only.

for non-ductile walls only.

RW200C Double Reinforcement Minimum Reinforcement

RW200C##		Vertical Bars - Each Face (min. N12-350)			
Allowable Bars		N12	N16	N20	N24 ¹
Horizontal (min. N12-350)	N12	Acceptable	Acceptable	Acceptable	With Caution
	N16	Acceptable	Acceptable	With Caution	Not Recommended
	N20	With Caution	With Caution	With Caution	Not Recommended
	N24	Not Recommended	Not Recommended	Not Recommended	Not Recommended

Double layer if specified by project engineer.

Horizontal Bar Spacing 233/350

Vertical Bar Spacing 150 to 350

1N24 One side only, N16 max other side.

Acceptable
With Caution
Not Recommended


RW200C Double Reinforcement Out of Plane Flexural Capacity (ϕM_u kNm/m) ($N^*=0$)

Vertical Bars*	d	ρ^*	25 MPa	32 MPa	40 MPa	50 MPa	65 MPa#
N12@300	145	0.0026	21.09	–	–	–	–
N12@250	145	0.0031	25.14	25.36	25.51	–	–
N16@400	143	0.0035	27.43	27.7	27.88	28.04	–
N16@350	143	0.004	31.15	31.5	31.74	31.94	32.13
N16@300	143	0.0047	36.04	36.51	36.84	37.11	37.36
N16@250	143	0.0056	42.73	43.4	43.89	44.28	44.63
N16@200	143	0.0071	52.44	53.5	54.25	54.86	55.42
N20@300	141	0.0074	53.56	54.71	55.54	56.19	56.8
N20@250	141	0.0089	63.02	64.67	65.85	66.8	67.67
N20@200	141	0.0112	76.4	78.99	80.84	82.32	83.68
$\rho_{st,min}$ [8.1.6.1.(2)]			0.0023	0.0026	0.0029	0.0033	0.0037

$\phi M_u = \phi(f_y \rho b d^2 (1 - 0.6 \rho f_y / f'_c))$
 *Tension bars one face.
 # for non-ductile walls only.

RW200C Double Reinforcement Lintels with Vertical PVC Webs

UDL capacity of a simple standard double reinforcement lintel with minimum reinforcement other than extra top and bottom bars shown. Designer can utilise the slab over as T-beam, extra horizontal or vertical shear reinforcement if extra strength is required.



RW200C Double Reinforcement Lintels with Vertical PVC Webs w*(kN/m)

D	2N12 Top & Bottom, Depth (mm)				2N16 Top & Bottom, Depth (mm)			
	150	300	450	750	150	300	450	750
Span (mm)								
3600	9.3	19.5	29.7	50.1	14.1	27.4	40.9	72.6
3300	11.0	23.2	35.3	59.6	15.5	30.4	46.0	84.7
3000	13.3	28.0	42.7	72.1	17.2	34.2	52.6	101.6
2700	16.5	34.6	52.7		19.3	39.1	61.3	
2400	20.8	43.8	66.7		22.1	45.6	73.6	
2100	25.8	54.7	87.2		25.8	54.7	92.0	
1800	30.9	68.4			30.9	68.4		
1500	38.7	91.2			38.7	91.2		
1200	51.5				51.5			
900	77.3				77.3			

= ϕV_{uc} governs, otherwise ϕM_u
 = Design to AS3600–2018 Sect 12

RW200C Double Reinforcement In-plane Shear Along Vertical PVC Webs


RW200C Double Reinforcement PVC Profile/Spacing

t_w	S_{punch}	N_{layers}	A_c	Align	Bar Max	Min Reo	Max Spacing	$t_{w,\text{shear}}$	μ	k_{co}
195	117	2	50.1%	100%	16	0.0025	350	97.7	0.36	0.20

RW200C Double Reinforcement In Plane Shear along Vertical PVC Web ϕV_u (kN/m)


Horizontal Bars	ρ	25 MPa	32 MPa	40 MPa	50 MPa	65 MPa [#]
2N12@350	0.0033	175.1	183.8	192.6	202.4	215.5
2N12@233	0.0050	230.0	238.6	247.4	257.3	270.5
2N16@350	0.0059	260.2	268.8	277.6	287.5	300.5
2N16@233	0.0088	357.7	366.3	375.1	385.0	398.1
2N16@117	0.0176	366.4	468.9	586.2	674.2	687.3
Max. Shear		366.4	468.9	586.2	732.7	732.7
$\phi V_u = \phi(\mu \rho t_w f_y + k_{co} t_w f'_{ct})$						
$\phi V_{\text{max}} = \phi 0.2 f'_c t_w \text{ shear} < \phi 10 t_w \text{ shear}$						
[#] for non-ductile walls only.						

RW256S Structural Capacities



RW256S Axial Capacity ϕN_u (kN/m)

t_w	t_{fire}	S_{web}	S_{punch}	A_c	N_{layers}	d_h	$f'_{c,max}$
251	251	73.5	240	51.3%	2	42.7	65



$k = 0.75$		Continuous Floor $e = 0.05 t_w$					Discontinuous Floor $e = 1/6 t_w$				
H_{wu}	H_{we}	25 MPa	32 MPa	40 MPa	50 MPa	65 MPa*#	25 MPa	32 MPa	40 MPa	50 MPa	65 MPa*#
6000	4500	1543	1975	2468	3085	4011	1226	1570	1962	2453	3188
5000	3750	1720	2202	2752	3440	4472	1404	1797	2246	2808	3650
4500	3375	1797	2300	2875	3593	4671	1480	1895	2369	2961	3849
4200	3150	1839	2354	2942	3678	4781	1523	1949	2436	3045	3959
3900	2925	1878	2404	3005	3756	4883	1562	1999	2499	3124	4061
3600	2700	1914	2450	3063	3829	4977	1598	2046	2557	3196	4155
3300	2475	1948	2493	3116	3895	5064	1631	2088	2610	3263	4242
3000	2250	1978	2532	3165	3956	5143	1662	2127	2659	3324	4321
2700	2025	2006	2567	3209	4012	5215	1690	2163	2703	3379	4393
2400	1800	2031	2599	3249	4061	5279	1714	2194	2743	3429	4457
2100	1575	2052	2627	3284	4105	5336	1736	2222	2778	3472	4514
1800	1350	2071	2651	3314	4142	5385	1755	2246	2808	3510	4563
Limit with bottom plate		2362	3024	3780	4725	6142	2362	3024	3780	4725	6142

* for $f'_c > 50$ MPa, CSR appointed installer only.

for non-ductile walls only.

RW256S Minimum Reinforcement

RW256S		Vertical Bars - Each Face (min. N12-350)				
Allowable Bars		N12	N16	N20	N24	N28
Horizontal (min. N12-350)	N12					
	N16					
	N20					
	N24					

Horizontal Bar Spacing 240
Vertical Bar Spacing 150 to 350

Acceptable
With Caution
Not Recommended


RW256S Out of Plane Flexural Capacity ϕM_u (kNm/m) ($N^*=0$)

Vertical Bars*	d	ρ^*	25 MPa	32 MPa	40 MPa	50 MPa	65 MPa#
N12@250	194	0.0023	34.13	–	–	–	–
N16@400	192	0.0026	37.42	37.69	–	–	–
N16@350	192	0.003	42.57	42.91	43.16	–	–
N16@300	192	0.0035	49.35	49.83	50.16	50.43	50.68
N16@250	192	0.0042	58.71	59.39	59.87	60.26	60.62
N16@200	192	0.0052	72.42	73.48	74.23	74.84	75.4
N20@300	190	0.0055	74.37	75.52	76.34	77	77.61
N20@250	190	0.0066	87.98	89.64	90.82	91.77	92.64
N20@200	190	0.0083	107.61	110.2	112.05	113.53	114.9
N24@250	188	0.0096	120.42	123.85	126.3	128.26	130.07
N24@200	188	0.012	145.62	150.98	154.81	157.87	160.7
N24@150	188	0.016	183.26	192.79	199.6	205.05	210.08
$\rho_{st,min}$ [8.1.6.1.(2)]			0.0021	0.0024	0.0027	0.0030	0.0034

$\phi M_u = \phi(f_y \rho b d^2 (1 - 0.6 \rho f_y / f'_c))$
 *Tension bars one face
 #for non-ductile walls only

RW256S Standard Double Reinforcement Lintels with Vertical PVC Webs

UDL capacity of a simple standard double reinforcement lintel with minimum reinforcement other than extra top and bottom bars shown. Designer can utilise the slab over as T-beam, extra horizontal or vertical shear reinforcement if extra strength is required.



RW256S Standard Double Reinforcement Lintels with Vertical PVC Webs w^* (kN/m)

D	2N12 Top & Bottom, Depth (mm)				2N16 Top & Bottom, Depth (mm)			
	150	300	450	750	150	300	450	750
Span (mm)								
3600	9.5	19.7	29.9	50.3	15.7	33.8	50.8	88.0
3300	11.3	23.4	35.5	59.8	18.7	37.8	57.2	104.7
3000	13.6	28.3	43.0	72.4	21.4	42.5	65.4	126.4
2700	16.8	35.0	53.1		24.0	48.6	76.3	
2400	21.3	44.2	67.2		27.5	56.7	91.5	
2100	27.8	57.8	87.8		32.0	68.0	114.4	
1800	37.9	78.7			38.5	85.1		
1500	48.1	113.3			48.1	113.4		
1200	64.1				64.1			
900	96.1				96.1			

= ϕV_{uc} governs, otherwise ϕM_u
 = Design to AS3600–2018 Sect 12

RW256S In-plane Shear Along Vertical PVC Webs

RW256S PVC Profile/Spacing

t_w	S_{punch}	N_{layers}	A_c	Align	Bar Max	Min Reo	Max Spacing	$t_{w,\text{shear}}$	μ	k_{co}
251	240	2	48.6%	100%	20	0.0025	350	121.5	0.35	0.19

RW256S In Plane Shear along Vertical PVC Web $\emptyset V_u$ (kN/m)


Horizontal Bars	ρ	25 MPa	32 MPa	40 MPa	50 MPa	65 MPa [#]
2N12@360	0.0025	185.0	195.8	206.7	219.0	235.2
2N12@240	0.0038	236.5	247.2	258.2	270.4	286.7
2N16@360	0.0045	265.2	275.9	286.9	299.1	315.4
2N16@240	0.0067	356.8	367.5	378.5	390.7	407.0
2N20@360	0.0070	368.1	378.9	389.9	402.1	418.4
2N20@240	0.0105	455.6	522.0	532.9	545.2	561.4
2N16@120	0.0134	–	583.2	653.2	665.5	681.7
2N20@120	0.0209	–	–	729.0	911.3	911.3
Max. Shear		455.6	583.2	729.0	911.3	911.3

$$\emptyset V_u = \emptyset (\mu \rho t_w f_y + k_{co} t_w f'_{ct})$$

$$\emptyset V_{\text{max}} = \emptyset 0.2 f'_c t_w \text{ shear} < \emptyset 10 t_w \text{ shear}$$


for non-ductile walls only.

RW275S Structural Capacities



RW275S Axial Capacity ϕN_u (kN/m) Non-Ductile (2-Layers)

t_w	t_{fire}	S_{web}	S_{punch}	A_c	N_{layers}	d_h	$f'_{c,max}$
270	270	79	240	51.8%	2	41	65



$k = 0.75$		Continuous Floor $e = 0.05 t_w$				Discontinuous Floor $e = 1/6 t_w$			
H_{wu}	H_{we}	25 MPa	32 MPa	40 MPa	50 MPa	25 MPa	32 MPa	40 MPa	50 MPa
6000	4500	1671	2139	2674	3342	1329	1701	2126	2657
5000	3750	1863	2385	2981	3727	1521	1947	2433	3042
4500	3375	1946	2491	3114	3893	1604	2053	2566	3208
4200	3150	1992	2550	3187	3984	1649	2111	2639	3299
3900	2925	2035	2604	3255	4069	1692	2166	2707	3384
3600	2700	2074	2655	3318	4148	1731	2216	2770	3463
3300	2475	2110	2701	3376	4220	1767	2262	2828	3535
3000	2250	2143	2743	3429	4286	1800	2305	2881	3601
2700	2025	2173	2781	3477	4346	1830	2343	2929	3661
2400	1800	2200	2816	3520	4399	1857	2377	2971	3714
2100	1575	2223	2846	3557	4447	1881	2407	3009	3761
1800	1350	2244	2872	3590	4488	1901	2433	3042	3802
Limit with bottom plate		2362	3024	3780	4724	2362	3024	3780	4724

RW275S Minimum Reinforcement


RW275S		Vertical Bars - Each Face (min. N12-330)				
Allowable Bars		N12	N16	N20	N24	N28
Horizontal (min. N12-350)	N12					
	N16					
	N20					
	N24					

Horizontal Bar Spacing 240
Vertical Bar Spacing 150 to 350

Acceptable
With Caution
Not Recommended

RW275S Standard Double Reinforcement Lintels with Vertical PVC Webs

UDL capacity of a simple standard double reinforcement lintel with minimum reinforcement other than extra top and bottom bars shown. Designer can utilise the slab over as T-beam, extra horizontal or vertical shear reinforcement if extra strength is required.



RW275S Standard Double Reinforcement Lintels with Vertical PVC Webs w*(kN/m)

	2N12 Top & Bottom, Depth (mm)				2N16 Top & Bottom, Depth (mm)			
D	150	300	450	750	150	300	450	750
Span (mm)								
3600	9.5	19.7	29.9	50.3	15.9	34.0	52.0	88.1
3300	11.3	23.5	35.6	59.9	18.9	40.4	61.9	104.9
3000	13.7	28.4	43.1	72.5	22.9	48.8	74.9	126.9
2700	16.9	35.1	53.2		27.6	55.7	87.4	
2400	21.4	44.4	67.3		31.5	65.0	104.9	
2100	28.0	57.9	87.9		36.8	78.0	131.2	
1800	38.1	78.9			44.1	97.5		
1500	54.8	113.6			55.1	130.1		
1200	73.5				73.5			
900	110.3				110.3			
	= ϕV_{uc} governs, otherwise ϕM_u							
	= Design to AS3600–2018 Sect 12							

RW275S In-plane Shear Along Vertical PVC Webs


RW275S PVC Profile/Spacing

t_w	S_{punch}	N_{layers}	A_c	Align	Bar Max	Min Reo	$t_{w, shear}$
269	240	2	51.8%	100.0%	20	0.0025	139.3

RW275S In Plane Shear along Vertical PVC Web ϕV_u (kN/m)


Horizontal Bars	ρ	25 MPa	32 MPa	40 MPa	50 MPa	65 MPa [#]
2N12@240	0.0035	258.7	271.0	283.6	297.6	316.3
2N16@360	0.0042	289.3	301.6	314.2	328.2	346.9
2N16@240	0.0062	386.9	399.2	411.8	425.8	444.5
2N20@360	0.0065	399.0	411.4	423.9	438.0	456.6
2N20@240	0.0097	522.5	563.9	576.4	590.5	609.1
2N16@120	0.0125	–	668.8	704.6	718.7	737.3
2N20@120	0.0195	–	–	836.1	1045.1	1045.1
Max. Shear		522.5	668.8	836.1	1045.1	1045.1
$\phi V_u = \phi(\mu \rho t_w f_y + k_{co} t_w f'_{ct})$						
$\phi V_{max} = \phi 0.2 f'_c t_w shear < \phi 10 t_w shear$						
[#] for non-ductile walls only.						

RW300S Structural Capacities



RW300S Axial Capacity ϕN_u (kN/m) Non-Ductile (Layers)

t_w	t_{fire}	S_{web}	S_{punch}	A_c	N_{layers}	d_h	$f'_{c,max}$
295	295	79	240	51.8%	2	41	65



k = 0.75		Continuous Floor $e = 0.05 t_w$				Discontinuous Floor $e = 1/6 t_w$			
H_{wu}	H_{we}	25 MPa	32 MPa	40 MPa	50 MPa	25 MPa	32 MPa	40 MPa	50 MPa
6000	4500	2223	2845	3557	4446	1814	2321	2902	3627
5000	3750	2384	3051	3814	4768	1974	2527	3159	3949
4500	3375	2453	3140	3925	4907	2044	2616	3270	4088
4200	3150	2492	3189	3986	4983	2082	2665	3331	4164
3900	2925	2527	3235	4043	5054	2118	2710	3388	4235
3600	2700	2560	3277	4096	5120	2150	2753	3441	4301
3300	2475	2590	3315	4144	5180	2181	2791	3489	4361
3000	2250	2618	3351	4189	5236	2208	2827	3533	4417
2700	2025	2643	3383	4229	5286	2233	2859	3573	4467
2400	1800	2665	3412	4264	5331	2256	2887	3609	4512
2100	1575	2685	3437	4296	5370	2276	2913	3641	4551
1800	1350	2702	3459	4323	5404	2293	2935	3668	4585
Limit with bottom plate		2915	3731	4664	5830	2915	3731	4664	5830

RW300S Minimum Reinforcement


RW300S		Vertical Bars - Each Face (min. N12-330)				
Allowable Bars		N12	N16	N20	N24	N28
Horizontal (min. N12-350)	N12					
	N16					
	N20					
	N24					

Horizontal Bar Spacing 240
Vertical Bar Spacing 150 to 350

Acceptable
With Caution
Not Recommended

RW300S Standard Double Reinforcement Lintels with Vertical PVC Webs

UDL capacity of a simple standard double lintel with minimum reinforcement other than extra top and bottom bars shown. Designer can utilise the slab over as T-beam, extra horizontal or vertical shear reinforcement if extra strength is required.



RW300S Standard Double Reinforcement Lintels with Vertical PVC Webs w*(kN/m)

	2N12 Top & Bottom, Depth (mm)				2N16 Top & Bottom, Depth (mm)			
D	150	300	450	750	150	300	450	750
Span (mm)								
3600	9.5	19.7	29.9	50.3	15.9	34.0	52.1	88.2
3300	11.3	23.5	35.6	59.9	19.0	40.5	62.0	104.9
3000	13.7	28.4	43.1	72.5	23.0	49.0	75.0	127.0
2700	16.9	35.1	53.2		28.1	56.8	89.1	
2400	21.4	44.4	67.3		32.1	66.2	106.9	
2100	28.0	58.0	88.0		37.4	79.5	133.6	
1800	38.1	78.9			44.9	99.4		
1500	54.9	113.6			56.2	132.5		
1200	74.9				74.9			
900	112.3				112.3			

= ϕV_{uc} governs, otherwise ϕM_u
 = Design to AS3600–2018 Sect 12

RW300S In-plane Shear Along Vertical PVC Webs

RW300S PVC Profile/Spacing

t_w	S_{punch}	N_{layers}	A_c	Align	Bar Max	Min Reo	$t_{w, shear}$
274	240	2	51.8%	100%	20	0.0025	141.9

RW300S In Plane Shear along Vertical PVC Web ϕV_u (kN/m)

Horizontal Bars	ρ	25 MPa	32 MPa	40 MPa	50 MPa	65 MPa [#]
2N12@240	0.0034	260.4	273.0	285.8	300.1	319.1
2N16@360	0.0041	291.0	303.6	316.4	330.7	349.7
2N16@240	0.0061	388.6	401.2	414.0	428.3	447.3
2N20@360	0.0064	400.8	413.4	426.2	440.5	459.5
2N20@240	0.0095	532.2	565.8	578.6	592.9	611.9
2N16@120	0.0122	–	681.3	706.8	721.2	740.1
2N20@120	0.0191	–	–	851.6	1050.4	1064.5
Max. Shear		532.2	681.3	851.6	1064.5	1064.5
$\phi V_u = \phi(\mu \rho t_w f_y + k_{co} t_w f'_{ct})$						
$\phi V_{max} = \phi 0.2 f'_c t_w shear < \phi 10 t_w shear$						
# for non-ductile walls only.						

Non-Ductile Wall Detailing

Standard AFS Wall Detailing for Non-Ductile Wall Designs in accordance with AS3600-2018 Section 2.2

and the relevant clauses in Section 14.4.

Junctions

In general Wall Junctions are not required to transfer of in plane Lateral or Shear loads across the junctions. Where transfer of in-plane Lateral or Shear loads across junctions is required the Project Engineer is

to specify the AFS Special Junction Details on the Structural Documentation. If detailing is required beyond these special junctions AFS Technical Support is to be consulted and detailing reviewed.

Standard wall junctions

Standard junctions are used except where the structural documentation indicates otherwise. Core Walls would generally be specified with special Junctions.

Reinforcement Detailing Constraints – Single Reinforcement

Fig A1: Cross Wall Junction




Fig A2: Corner 90°




Fig A3: T Wall Junction





Fig A4: Standard Hook Bars



Standard Hook Bar

Reo	D	L	Hook	Lap	RW110C	RW156C	RW200C
N12	72	550	70	450	Y	Y	Y
N16	96	700	70	600	N	N	Y
N20	120	1000	80	900	N	N	Y

Reinforcement Detailing Constraints – Double Reinforcement

Fig A5: Cross Wall Junction




Fig A6: Corner 90°




Fig A7: Corner 90°






Fig 8. T Wall Junction



Standard U Bar

Wall	Reo	Lap	D	L
RW200C	N12	450	105	750
RW256S	N12	450	155	750
RW256S	N16	600	155	900
RW275S	N12	450	175	750
RW275S	N16	600	175	900
RW300S	N12	450	205	750
RW300S	N16	600	205	900

Fig 9. Standard U Bars




Non-Ductile Blade Walls/Columns

AFS uses the following definitions for Blade Walls/Columns, with typical standardised reinforcement detailing that is compliant to AS3600-2018

Blade walls

Blade walls are short walls designed as non-ductile walls without ligatures in accordance with Section 11 of AS3600-2018. They are generally loaded concentrically, with concrete strength not greater than 50MPa and have no net tension in the strong or weak axis.


Fig A10: Rediwall® Blade Wall



Blade Columns

Are short wall designed as columns with ligatures to AS3600-2018 Sections 14 and 10.


Fig A11: Rediwall® Blade Column



Joints

The structural concrete wall effectively has 'control joints' at each plastic web so no additional crack control joints are necessary. Full depth "movement joints" may be required depending on the geometry of the structure and other considerations such as thermal loads, exposure and building joints. Movement joints shall be placed in locations nominated by the structural engineer and must be documented on structural drawings. These will be installed at construction stage by the rediwall® installation contractor. As a guide the engineer should review joint reinforcement requirements for wall runs longer than 16 metres. Refer to Fig A12.

Fig A12: Movement Joint Non-Ductile Design Detail



Note: Can be dowel jointed if required structurally. Must be clearly specified and negotiated with installers at time of tender. Installed where nominated by project engineer. Must be clearly documented on drawings.

Limited Ductile Wall Design

Limited Ductile Design


AFS Rediwall® can be designed to the requirements of AS3600-2018 Limited Ductile Walls. Limited Ductile Walls are to be designed to Section 2.2, Clause 14.4 and Clause 14.6 of AS3600-2018. Clause 14.6.1 requires the Limited Ductile walls to have reinforcement on each face and be detailed in accordance with the requirements of Clause 14.6.

Refer to the following sections for standard detailing to suit Rediwall® Limited Ductile Walls with boundary elements.

It is recommended that AFS Limited Ductile Walls are only to be installed by experienced installers due to the additional detailing requirements. AFS detailing is to be used unless AFS Technical Support reviews and approves alternate detailing.

Below is a sample Moment Interaction curve showing RW200C capacity without core confinement.

Fig D13: Sample Moment Interaction



Limited Ductile Design Examples

The following tables provides other design examples for Rediwall® sizes over a range of reinforcement and concrete strengths.













RW200C Panel	Plan	Elevation
		
RW256S Panel	Plan	Elevation
		
RW275S Panel	Plan	Elevation
		
RW300S Panel	Plan	Elevation
		

TABLE A2: Rediwall® Panel Properties

Wall Type	t_w	S_{web}	S_{punch}	N_{layers}	A_c	Slender. Limit	d_h	Min Reo	$f'_{c,max}$
RW200C	195	66.6	116.7	2	50.1%	30	39	N12-350hor. N12-300 vert.	50
RW256S	250	73.5	240	2	48.6%	30	45	N12-350hor. N12-300 vert.	50
RW275S	269	75.0	240	2	51.8%	30	45	N12-233hor. N12-300 vert.	50
RW300S	274	75.0	240	2	51.8%	30	45	N12-233hor. N16-300 vert.	50

TABLE A3: Rediwall® Design Axial Forces

Wall Description	C11.7.4 restraints not required	H_{wu} $k = 0.75$ mm	t_w mm	d_c mm	p_{vert} %	ϕN_u kN/m	14.3.2.1 $0.20 \cdot f'_c$ kN/m	ϕM_u kNm/m
RW200C (194), 32MPa, N12-300 vert. Each Face, N12 hor.	Each Face ($\leq 1\%$)	3000	194	50.5	0.39	1760	1242	31
RW200C (194), 50MPa, N16-200 vert. Each Face, N12 hor.	Each Face ($\leq 1\%$)	3000	194	52.5	1.0	2730	1455	65
RW200C (194), 50MPa, N20-175 vert. Each Face, N12 hor.	EF Tens. Only	3000	194	54.5	1.9	2930	1455	69
RW256S (250), 32MPa, N12-300 vert. Each Face, N12 hor.	Each Face ($\leq 1\%$)	3000	250	56.8	0.30	3040	1200	52
RW256S (250), 50MPa, N20-250 vert. Each Face, N12 hor.	Each Face ($\leq 1\%$)	3000	250	60.8	1.0	4820	1875	110
RW256C (250), 50MPa, N28-200 vert. Each Face, N16 hor.	EF Tens. Only	3000	250	66.8	2.5	5440	1875	125
RW275S (269), 32MPa, N12-250 vert. Each Face, N12 hor.	Each Face ($\leq 1\%$)	3000	269	57	0.34	3470	1291	62
RW275S (269), 50MPa, N28-200 vert. Each Face, N16 hor.	EF Tens. Only	3000	269	67	2.3	6150	2018	148
RW300S (294), 32MPa, N16-300 vert. Each Face, N12 hor.	Each Face ($\leq 1\%$)	3000	294	45	0.46	4110	1411	82
RW300S (294), 50MPa, N28-200 vert. Each Face, N16 hor.	EF Tens. Only	3000	294	45	2.1	7370	2205	209

Limited Ductile Wall Detailing

Standard afs rediwall® Detailing for Limited Ductile Wall Designs in accordance with AS3600-2018 Section 2.2 and Clauses in 14.4 and 14.6. All limited Ductile Walls will have 2 layers of reinforcement.

In general wall fitments are not used in afs rediwall® when designed in accordance to AS3600-2018 Clause 14.6 with $f'_c \leq 50$ MPa. If fitments are required in small areas outside of boundary elements consult the AFS Technical Support for assistance.

Boundary Elements

AS3600-2018 Cl14.6.2 Boundary Elements requires boundary elements where extreme fibre compressive stress exceeds $0.15 f'_c$. The extent and detailing of the boundary elements are to be determined by the designer.

AFS Rediwall® Boundary Elements have special installation requirements and are only to be installed by AFS approved experienced installers. AFS detailing is to be used unless AFS Technical Support reviews and approves alternate detailing.

Structures not more the four stories

“For structures not more than four stories above their structural base and where boundary elements are required” [AS3600 Cl14.6.2.2] the AFS standard end detail may be used as the boundary element.

AFS Standard Boundary Element will be used at all Boundaries unless specified in the Project Documentation.

Reinforcement

In accordance with AS3600-2018 Cl14.6.7 maximum vertical reinforcement for afs rediwall® shall be 2.1% (Half $21/f_{sy}$) including areas with boundary elements and laps. Minimum horizontal and vertical reinforcement shall be 0.0025.

Fig A14: AFS Rediwall® Standard Boundary Element





Fig A15: AFS Rediwall® Standard Boundary Element (Alternate Detail)



Structures more than four stories

For structures more than four stories CI14.6.2.3 requires boundary elements to conform to CI10.7.4. The AFS Standard Boundary Element below can be installed during installation of the walls.

Fig A16: AFS Standard Boundary Element > 4 Storeys






Fig A17: Standard U Bars



Standard U Bar

Wall	Reo	Lap	D	L
RW200C	N12	450	105	750
RW256S	N12	450	155	750
RW256S	N16	600	155	900
RW275S	N12	450	175	750
RW275S	N16	600	175	900
RW300S	N12	450	205	750
RW300S	N16	600	205	900

Fig A18: Standard Hook Bars




Standard Hook Bar

Reo	D	L	Hook	Lap	RW110C	RW156C	RW200C
N12	72	550	70	450	Y	Y	Y
N16	96	700	70	600	N	N	Y
N20	120	1000	80	900	N	N	Y

Boundary elements closed fitments are to be spaced vertically in accordance with Cl 14.6.2 of AS3600-2018 as follows:

- Spaced at lesser of t_w and 200mm
- For structures more than four stories as per Cl 14.6.2.3 of AS3600-2018.

Fig A19: AFS Limited Ductile Core Wall Detailing




Note: Hooked U-bars may be used in lieu of closed ligatures.

Limited Ductile Wall Horizontal Reinforcement Wall Laps

AFS recommends Fig 14.6.7(D) of AS360-2018 only be used where required. Alternatives to the 14.6.7 detail are:

- Construction joints to split the walls and prevent transfer of in-plane lateral and shear loads.

Fig A20: 14.6.7(D) Horizontal Wall Bar Lap Detail




Blade Columns

Blade Columns

Are short wall designed as columns with ligatures to AS3600-2018 Sections 14 and 10.

Fig A21: Rediwall® Blade Column



Junctions

AFS Standard Junctions

Standard Junctions are not to be used with Limited Ductile Walls. Junction Joints may be used to structurally isolate walls either side of the junction and prevent transfer of in-plane forces

AFS Special Junctions

Structural Documentation is to specify where Special Junctions are to be used. If detailing is required beyond these special junctions AFS Technical Support is to be consulted and detailing reviewed.

Special Limited Ductile Junction Details –Without Boundary Elements

Fig A22: Corner Type 1





Fig A23: T junction




Movement Joints

Movement Joints will be required over any building joints and where specified on the Project Documentation

The structural concrete wall effectively has control joints at each stud so no additional crack control joints are necessary. Full depth "movement joints" may be required depending on the geometry of the structure and other considerations such as thermal loads,

exposure and building joints. In general "movement joints" would not be required for walls less than 16m long. Structural movement joints will be placed in locations nominated by the structural engineer and must be documented on structural drawings. These will be installed at construction stage by the afs rediwall® installation contractor.

Fig A24: Rediwall® Movement joint




Note: Installed where nominated by project engineer. Must be clearly documented on drawings. Typically not required in walls less than 16m in length.

Construction Joint

Construction Joints can be used wherever a pour break is required, walls may be split to prevent transfer

of in-plane forces. Locations are to be specified on the Project Documentation.

Fig A25: Rediwall® Construction Joint



Wall Junctions Joints

Junction Joints to structurally isolate walls either side of the junction and prevent transfer of inplane forces.

Fig A26: Rediwall® Corner Joint





Fig A27: Rediwall® T joint



Temporary Works

Temporary works are to be detailed by the project designers to suit the project design and conditions. AFS standard bracing details may be used subject to the limitations given on the drawing and certifications. Refer to Appendix – AFS Standard Bracing Drawings.

AFS standard bracing is to be installed in accordance with the standard bracing drawings and Volume 3 – 'Rediwall® Installation Guide – Rediwall Temporary Construction Bracing'. For further information on AFS standard bracing, please contact AFS Technical Services.

Core Filling of Walls

Introduction

AFS Rediwall® cannot be filled with concrete using traditional concrete mixes. The concrete mix and concrete placement technique is critical to the successful outcome of filling rediwall®.

AFS has carried out tests which achieved desired compaction and dense, homogeneous coverage of afs rediwall®.

This guide sets out the methods used by AFS to achieve suitable compaction.

The contractor or installer is responsible for achieving compaction and dense, homogeneous coverage of the concrete mix in Rediwall®. AFS accepts no responsibility for achieving compaction of the concrete in afs rediwall® or core filling of walls.

Concrete Pour Limitations

When panel installation is complete and all appropriate bracing and checks completed, the walls can be filled with concrete.

The quantity of concrete that can be poured in a day must be assessed and determined in consideration of the following factors:

- Ease of access
- Number of passes (or lifts) that are required
- Concrete gelling time between passes
- Consideration of wet weather

For wet weather, on-site conditions should be assessed and the concrete pour either be delayed or be undertaken with caution, applying measures to suit the given conditions.

Additional Equipment Required for Concrete Pour

Prior to commencing a pour, ensure that a concrete vibrator with flexible shaft and 38mm head is ready for use, and that multiple shovels, trowels, screw guns, screws and at least one wheelbarrow are readily available.

Concrete Mix Design

The following afs concrete mix guide shall be used together with concrete placement in accordance with Volume 3 – 'rediwall® Installation Guide' to achieve the requirements of AS3600 – 2018. Reputable concrete suppliers have standard mix designs to achieve these requirements.

Rediwall® Concrete Mix Design Guide

	AFS Rediwall® (Refer to Structural Engineer for Mix specification)				
Strength $f'c$ (MPa)	S25	S32	S40	S50	S65
Target Installation Slump	180±20	180±20	180±20	180±20	180±20
Design Slump (mm)	180	180	180	180	180
Maximum W/C Ratio	0.7	0.6	0.45	0.4	0.35
Nominal Fine to Total Aggregate Percentage (%)	65	60	55	50	50
Maximum Aggregate Size (mm)	10	10	10	10	10
Maximum 56 Day Drying Shrinkage (µm)	1000	1000	1000	1000	1000
Hanson Recommended Admixtures	WRPAPN20 (WR) ex Grace, ADVA-142 (HWR) ex Grace, or equivalent				

Notes:

- For higher on-site temperature environments slump at the batching plant may be varied to suit these conditions.
- Site water is allowed to be used to reach desired installation slump however, the maximum W/C ratio must not be exceeded.
- Due to local raw material availability, characteristics will vary significantly, refer to Project Engineer for further details.
- The addition of all admixtures are typically dosed at the beginning of the batch.
- Concrete mix should have a typical 'Gel' time of 30-60min in accordance with the Gel Test detailed in this guide.

Performance

The afs rediwall® system has Codemark Certification to confirm that it can be designed, detailed and installed to satisfy the relevant requirements of NCC 2019 Amendment 1. These include the following:

Section C. Fire Resistance:

- CP1 Structure stability
- CP2 Avoid spread of fire
- CP3 Protect from spread of fire and smoke in patient care and aged care buildings
- CP4 Material and assembly
- CP7 Avoid spread of fire to emergency equipment
- CP8 Protect spread of fire to openings and penetrations

Section F. Health and Amenity

- FP1.4 Weatherproofing
- FP5.2 Sound transmission and insulation – Walls
- FP5.5 Sound transmission in insulation – Walls in age care buildings

Section G. Ancillary Provisions

- GP5.1 Construction in bush fire prone areas

Sections J. Energy efficiency

- JP1 Energy efficiency

Fire Testing

AFS Rediwall® has had extensive fire testing and fire assessments to provide supportive evidence to back the Rediwall® fire and non-combustibility compliance. This includes:

- AS5113 (BS8414) Facade Fire Test
- AS5637.1 Reaction of Fire Classification (AS/ISO9705 Room Fire Test)
- AS1530.4 Fire Resistance Levels (FRL) Test/Assessment
- AS1530.4 FRL Penetration Test/Assessment
- AS1530.3 Fire Hazard Properties Test

Fire Resistance Levels (FRL)s

Fire rating requirements of the NCC are specified in terms of Fire Resistance Levels (FRL). The FRL specifies the performance, in minutes, of the fire tested specimens for each of the following three design criteria when fire tested to the requirements of the Australian Standards AS1530 'Methods for Fire Test on Building Materials, Components and Structures' part 4 'Fire-Resistance Tests of Elements of Building Construction'.

- Structural adequacy
- Integrity
- Insulation

A wall system under fire test that carries its load for 240 minutes and maintains its integrity and insulation for 240 minutes is given a FRL of 240/240/240, i.e 240 minutes structural adequacy, 240 minutes integrity and 240 minutes insulation.

Systems constructed to the standard required for particular FRL may be used to satisfy the requirements of lesser FRL.

Rediwall may be determined in accordance with NCC using the FRL given in the CSIRO Fire Test Reports. Where the wall characteristics are outside the limits of the CSIRO Fire Test Reports the FRL may be determined by the standard methods in AS3600–2018.

TABLE A4: FRL by CSIRO Fire Test

Type	t_w	F'_c	H_w max	N^* max	FRL
	(mm)	(MPa)	(mm)	(kN)	(Ade/Int/Ins)
RW110C	105	32***	2700	152	90/90/90**
RW156C	150	32 ***	3000	333	240/240/240*
RW200C	195	32 ***	3000	333	240/240/240*
RW256S	250	32 ***	3000	333	240/240/240*
RW275S	270	32 ***	3000	333	240/240/240*
RW300S	295	32 ***	3000	333	240/240/240*

*FRL Determined by CSIRO Fire Test Report Number FCO3399

**FRL Determined by SGA Report 2013/277.65 R1.6

***S32 MPa afs concrete mix

TABLE A5: AS3600 FRP Structural Adequacy[^] – Exposed 1 Side

		60 Minutes	90 Minutes	120 Minutes	180 Minutes	240 Minutes	FRP Insulation ^{^^}
Wall	$t_{w,fire}$	$N^*f/\phi N_u$	$N^*f/\phi N_u$	$N^*f/\phi N_u$	$N^*f/\phi N_u$	$N^*f/\phi N_u$	Minutes
RW110C	105	0.26	0.09	–	–	–	90
RW156C	150	0.70	0.70	0.35	–	–	180
RW200C	195	0.70	0.70	0.70	0.53	–	240
RW256S	250	0.70	0.70	0.70	0.70	0.54	240
RW275S	269	0.70	0.70	0.70	0.70	0.69	240
RW300S	294	0.70	0.70	0.70	0.70	0.70	240

[^] FRP Structural Adequacy based on AS3600 – 2018, Table 5.7.2

^{^^} FRP Insulation based on CSIRO Test Report N° FCO3399

TABLE A6: AS3600 FRP Structural Adequacy[^] – Exposed 2 Side

		60 Minutes	90 Minutes	120 Minutes	180 Minutes	240 Minutes	FRP Insulation ^{^^}
Wall	$t_{w,fire}$	$N^*f/\phi N_u$	$N^*f/\phi N_u$	$N^*f/\phi N_u$	$N^*f/\phi N_u$	$N^*f/\phi N_u$	Minutes
RW110C	105	–	–	–	–	–	90
RW156C	150	0.70	0.50	0.20	–	–	180
RW200C	195	0.70	0.70	0.62	0.31	–	240
RW256S	250	0.70	0.70	0.70	0.60	0.35	240
RW275S	269	0.70	0.70	0.70	0.70	0.45	240
RW300S	294	0.70	0.70	0.70	0.70	0.54	240

[^] FRP Structural Adequacy based on AS3600 – 2018, Table 5.7.2

^{^^} FRP Insulation based on CSIRO Test Report N° FCO3399





Non-Combustibility – Wall Applications & Finishes









Rediwall® is compliant to the relevant parts of the Building Code of Australia (NCC2019 Amendment 1) for use within various non-combustible wall applications internally and externally for Classes 1, 10, and Class 2-9 buildings.






The following summaries of rediwall® internal and external wall applications with associated finishes have been assessed by Stephen Grubits & Associates, Fire Safety Engineer's Report 2013/277.78 R1.6 to be compliant with the relevant fire resistance performance requirements in NCC 2019 Amendment 1.

TABLE A7: Summary of compliance with Performance Requirements & Essential Safety Precautions

Rediwall® as Internal Wall Applications¹








Applications	Compliance with NCC Performance Requirements	Finishes	Safety Measures
Non-loadbearing fire resisting internal walls (Assessment 1A)	PVC formwork is not considered to affect compliance with CP2, CP3 and CP4	a. Unclad and PVC lining left in place 	No additional measures are required as fire spread and development of untenable conditions due to PVC formwork as well as over-cladding has been determined to be unlikely
Loadbearing fire resisting internal walls (Assessment 1B)	PVC formwork is not considered to affect compliance with CP1, CP2, CP3 and CP4		
Non-loadbearing non-fire resisting internal walls (Assessment 1C)	PVC formwork is not considered to affect compliance with CP3 and CP4	b. Cement render or similar non-combustible render finish over unclad rediwall® 	
Loadbearing non-fire resisting internal walls (Assessment 1D)	PVC formwork is not considered to affect compliance with CP3 and CP4		
Separating walls in Class 1 buildings (Assessment 1E)	PVC formwork is not considered to affect compliance with P2.3.1	c. Plasterboard lining directly affixed to surface of unclad rediwall® 	
Non-loadbearing fire walls (Assessment 2A)	PVC formwork is not considered to affect compliance with CP2, CP3 and CP4		
Loadbearing fire walls (Assessment 2B)	PVC formwork is not considered to affect compliance with CP1, CP2, CP3 and CP4	d. Plasterboard lining affixed to unclad rediwall®, using steel furring channels of specific orientation and spacing 	
Continued on next page...			










Applications	Compliance with NCC Performance Requirements	Finishes	Safety Measures
Non-loadbearing fire walls (Assessment 6A)	PVC formwork is not considered to affect compliance with CP1, CP2 and CP7	a. Unclad and PVC lining left in place  c. Plasterboard lining directly affixed to surface of unclad rediwall®  d. Plasterboard lining affixed to unclad rediwall®, using steel furring channels of specific orientation and spacing 	No additional measures are required as fire spread and development of untenable conditions due to PVC formwork as well as over-cladding has been determined to be unlikely
Internal lift shaft wall (internal face of the shaft wall) (Assessment 7A)	PVC formwork is not considered to affect compliance with CP1, CP2, CP3, CP4 and CP7	a. Unclad and PVC lining left in place 	No additional measures are required as fire spread and development of untenable conditions due to PVC formwork has been determined to be unlikely
Internal walls in fire isolated exits (Assessment 8A)	PVC formwork is not considered to affect compliance with CP1, CP2, CP3, CP4 and CP7	a. Unclad and PVC lining left in place  b. Cement render or similar non-combustible render finish over unclad rediwall®  c. Plasterboard lining directly affixed to surface of unclad rediwall®  d. Plasterboard lining affixed to unclad rediwall®, using steel furring channels of specific orientation and spacing 	No additional measures are required as fire spread and development of untenable conditions due to PVC formwork as well as over-cladding has been determined to be unlikely
Continued on next page...			








Applications	Compliance with NCC Performance Requirements	Finishes	Safety Measures
Internal walls in fire-control rooms (Assessment 9A)	PVC formwork is not considered to affect compliance with CP1, CP2, CP3, CP4 and CP7	a. Unclad and PVC lining left in place  b. Cement render or similar non-combustible render finish over unclad rediwall®  c. Plasterboard lining directly affixed to surface of unclad rediwall®  d. Plasterboard lining affixed to unclad rediwall®, using steel furring channels of specific orientation and spacing 	No additional measures are required as fire spread and development of untenable conditions due to PVC formwork as well as over-cladding has been determined to be unlikely
Service penetrations in fire resisting walls (Assessment 11A)	PVC formwork is not considered to affect compliance with CP2 and CP8	a. Unclad and PVC lining left in place 	Penetration in unclad and PVC lining left in place rediwall®, the PVC skin on the panel face is not considered to affect compliance with CP2 and CP8. For fire dampers, 6mm FC sheet to be fitted between wall face and damper frame extending 20mm beyond frame edge.

¹. This table is based on the Stephen Grubits & Associates rediwall Codemark Certification report, 2013/277.78 R1.6

TABLE A8: Summary of compliance with Performance Requirements & Essential Safety Precautions
Rediwall® as External Wall Applications¹

Applications	Compliance with NCC Performance Requirements	Finishes		Safety Measures
Non-loadbearing fire resisting external walls (Assessment 3A)	PVC formwork is not considered to affect compliance with CP2.	a. Unclad PVC lining left in place		No additional measures are required as fire spread and development of untenable conditions due to PVC formwork as well as over-cladding has been determined to be unlikely, subject to the following: – When applying finishes e, f or g, installation of an appropriate fire-stopping system ³ in the cavity is considered essential.
Loadbearing fire resisting external walls/spandrels (Assessment 3B)	PVC formwork is not considered to affect compliance with CP1 and CP2.	b. Non-combustible cement render or similar render finish over unclad Rediwall®		
Non-loadbearing non-fire resisting external walls (Assessment 4A)	PVC formwork is not considered to affect compliance with CP2.	e. Face brick with inner rediwall® skin forming a cavity wall		
Loadbearing fire resisting external walls/spandrels (Assessment 4B)	PVC formwork is not considered to affect compliance with CP1 and CP2.	f. Mechanically fixed tile system (<32kg/m²) to unclad rediwall®		
External walls above fire exits (Assessment 5A)	PVC formwork is not considered to affect compliance with CP1 and CP2.	g. Mechanically fixed non-combustible cladding to unclad rediwall®		The following safety measures are required when installing rediwall® above fire exit discharges: – When applying finishes e, f or g, installation of an appropriate fire-stopping system in the cavity is considered essential. – When unclad rediwall® (type a finish) or when applying finishes h or i, appropriate protection over/ near fire exit discharges as detailed in this assessment is required. ⁴ – When apply finish b, no additional measures are required.
		h. Direct-stick non-combustible cladding + adhesive to unclad rediwall®		
		i. Glue-fixed tile systems (<32kg/m²) + adhesive to unclad rediwall®		
Continued on next page...				

Applications	Compliance with NCC Performance Requirements	Finishes	Safety Measures
Retaining walls (external face of panel) (Assessment 10A)	PVC formwork is not considered to affect compliance with CP1 and CP2.	a. Unclad PVC lining left in place  j. With membrane 	No additional measures are required as fire spread and development of untenable conditions due to PVC formwork as well as over-cladding has been determined to be unlikely, subject to the following: – For finish j, the membrane is to be buried below ground.
Openings in fire resisting walls (Assessment 11B)	PVC formwork is not considered to affect compliance with CP1 and CP2.	a. Unclad PVC lining left in place  b. Non-combustible cement render or similar render finish over unclad rediwall®  e. Face brick with inner rediwall® skin forming a cavity wall  f. Mechanically fixed tile system (<32kg/m²) to unclad rediwall®  g. Mechanically fixed non-combustible cladding to unclad rediwall®  h. Direct-stick non-combustible cladding + adhesive to unclad rediwall®  i. Glue-fixed tile systems (<32kg/m²) + adhesive to unclad rediwall® 	No additional measures are required as fire spread and development of untenable conditions due to PVC formwork as well as over-cladding has been determined to be unlikely, subject to the following: – When applying finishes e, f or g, installation of an appropriate fire-stopping system ³ in the cavity is considered essential.
Continued on next page...			

Applications	Compliance with NCC Performance Requirements	Finishes	Safety Measures
<p>Rediwall® used externally at less than 2m above the ground (Assessment 12A)</p>	<p>PVC formwork is not considered to affect compliance with CP1 and CP2.</p>	<p>a. Unclad PVC lining left in place</p>  <p>b. Non-combustible cement render or similar render finish over unclad rediwall®</p>  <p>e. Face brick with inner rediwall® skin forming a cavity wall</p>  <p>f. Mechanically fixed tile system (<32kg/m²) to unclad rediwall®</p>  <p>g. Mechanically fixed non-combustible cladding to unclad rediwall®</p>  <p>h. Direct-stick non-combustible cladding + adhesive to unclad rediwall®</p>  <p>i. Glue-fixed tile systems (<32kg/m²) + adhesive to unclad rediwall®</p> 	<p>If the over-cladding extends beyond the extent of the rediwall®, installation of an appropriate fire-stopping system³ in the cavity at the top of the rediwall® over-cladding is considered essential.</p>

1. This table is based on the Stephen Grubits & Associates rediwall Codemark Certification report, 2013/277.78 R1.6

3. Installation of a fire-stopping system would include but is not limited to systems such as Rockwool™ cavity barrier, intumescent or steel cavity barrier or similar in between rediwall® external wall and cladding system where a continuous cavity from one floor to another floor is created. It is recommended that a fire-stopping product is to be installed where the continuous cavity starts and on the level of floor slab that is separating floors, in a horizontal manner.

4. Protection over/near external fire exits (i.e where rediwall® is installed over or near external fire exits) includes:

- Removal of the PVC lining, or
- Construction of a non-combustible overhead protection (e.g. awning) with the minimum requirements of:
 - Construction to be made of non-combustible material, and be able to resist the impact of falling debris, and
 - Projection of the overhead protection to be:
 - Parallel to the external wall with an overall width equal to the fire exit doorway width plus 300mm extending either side of the doorway, and
 - Extending a perpendicular distance of 3m minimum from the external wall.

Non-Combustibility – Specific Wall Applications

In addition to the general rediwall® applications with associated applied finishes, a number of specific rediwall® applications have also been assessed by Stephen Grubits & Associates, Fire Safety Engineers in Report 2013/277.78 R1.6 to confirm compliance with the relevant Performance Requirements, CP1, CP2, CP3, CP4, CP7 and CP8 of the NCC 2019 Amendment 1.

Rediwall® as a Boundary Wall

Based on the following arrangement, the rediwall® Boundary Wall has been assessed to achieve compliance to the relevant Performance Requirement CP1 and CP2 of the NCC 2019 Amendment 1.

This is achieved when unclad rediwall® is used as an external boundary wall and is located directly adjacent to an existing non-combustible fire resisting external boundary wall forming a cavity no greater than 50mm, there are no openings in either wall (unless it is a fire window as specified in the NCC), both walls can be of different height. The top and sides of the cavity space are to be fully enclosed by non-combustible flashing of appropriate size to suit the wall(s) configuration.

Fig A28: Rediwall® Boundary Wall Capping (elevation view)





Fig A29: Rediwall® Boundary Wall with Different Wall Heights



Fire Rated Junction (Internal Rediwall® to External Logicwall® or internal Rediwall® to internal Rediwall®)

When a junction is formed between a rediwall® (internal fire rated wall) and a Logicwall (external fire rated wall), or where a rediwall (internal fire rated wall) abutts end to end with another rediwall (internal fire rated wall), and the junction is required to be fire-resisting.

In order to seal the gap and maintain the appropriate integrity and insulation criteria of the FRL, fire-resisting sealant such as Fosroc Flamex, CSR FireSeal or similar that has been tested to AS1530.4 must be installed so that the sealant continuously fills the gap between the fibre cement face on each side of the junction and backing rod.

The required insulation and integrity FRL values are achieved by meeting the width and depth of the fire rated sealant as per the sealant manufacturer's specifications.

Based on these arrangement, rediwall® has been assessed to achieve compliance to the relevant Performance Requirements, CPI, CP2 and CP4 of the NCC 2019 Amendment 1. Refer to Fig A30.

Fig A30: Internal Rediwall® to External Logicwall Fire Rated Junction





Fig A31: Rediwall® to Rediwall® Fire Rated End Junction




Rediwall® Fire rated T-junction

A T-junction system incorporating the rediwall® T-Joiner (or floor track) is suitable to protect from the spread of fire across the junction. The joint is sealed by the concrete core which is filled so that it flows across the joint, and is strengthened by steel reinforcing across the joint.

Both walls are of the same FRL, each wall is expected to expand and deform at comparable rates when subjected to the heat of a fire. The concrete that bounds the joint is expected to act as a heat sink to any fire products passing through the junction. The concrete would therefore not permit the transfer of sufficient heat (either by radiation or by the transmission of hot gases) to enable ignition on the non-fire side of the rediwall®, thereby resisting fire spread between compartments.

Based on this particular arrangement, the rediwall has been assessed to achieve compliance to the relevant Performance Requirements, CPI, CP2, and CP4, of the NCC2019 Amendment 1.

Fig A32: Rediwall® T-Junction



Rediwall® Fire Rated Penetrations

AFS Rediwall® has been tested and assessed by CSIRO (test report FSV 2094 and assessment report FCO 3380) to AS1530.4 for fire resistance levels of various service penetrations to achieve up to FRL –/120/120 for service penetrations in the Rediwall® without the need to remove the PVC lining.

Service penetration types tested and assessed include:

- Clay Brick Infill
- Cable trays
- PVC Pipe work
- Electrical Cable (Single or bundled)
- Copper and metal pipe work
- Fire Dampers FRL –/120/– (Integrity)

These service penetrations types are allowed to be used through Rediwall® RW110C, RW156C, RW200C, RW256S, RW275S and RW300S with penetration apertures as close as 40mm spacing.

TABLE A9: AS1530.4 –Rediwall® Service Penetration FRL Rating and Protection Measures

Service Penetration Type	RW110C	RW156C, RW200C, RW256S RW275S, RW300S
Cable Trays or Bundled Cables	<p>FRL –/120/120</p> <p>Promat Supawrap PLUS</p> <p>Promat Promaseal A Sealant</p> <p>OR</p> <p>ANY sealant tested or assessed for FRL –/120/120 when protecting AS1530.4 appendix D1 Group A cable configurations in concrete walls 105mm thick or less.</p>	<p>FRL –/120/120</p> <p>Promat Supawrap PLUS</p> <p>Promat Promaseal A Sealant</p> <p>OR</p> <p>ANY sealant tested assessed for FRL –/120/120 when protecting AS1530.4 appendix D1 Group A cable configurations in concrete walls 150mm thick or less.</p>
Cables or PVC pipes	<p>FRL –/120/120</p> <p>Promat Promaseal FC100 Fire Collar</p> <p>OR</p> <p>ANY fire collar tested or assessed for FRL –/120/120 protecting plastic pipes in concrete walls 105mm thick or less</p>	<p>FRL –/120/120</p> <p>Promat Promaseal FC100 Fire Collar</p> <p>OR</p> <p>ANY fire collar tested or assessed for FRL –/120/120 protecting plastic pipes in concrete walls 150mm thick or less</p>
Copper Pipes or Metal Pipes	<p>FRL –/120/120</p> <p>Promat Supawrap & metal pipe clamps</p> <p>PLUS</p> <p>Promat Promaseal A Sealant (with sealant depth to 20mm in wall)</p> <p>OR</p> <p>ANY sealant tested in or assessed for FRL –/120/120 protecting AS1530.4 appendix E metal pipe configurations in concrete 105mm thick or less, (with increase sealant depth to 20mm into wall)</p>	<p>FRL –/120/120</p> <p>Promat Supawrap & metal pipe clamps</p> <p>PLUS</p> <p>Promat Promaseal A Sealant (with sealant depth to 20mm in wall)</p> <p>OR</p> <p>ANY sealant tested or assessed for FRL –/120/120 protecting AS1530.4 appendix E metal pipe configurations in concrete 150mm thick or less, (with increase sealant depth to 20mm into wall)</p>
Brickwork Infill	<p>FRL –/120/120</p> <p>Clay Bricks + Render infill in accordance to AS3700 with CSR Fireseal Sealant sealed perimeter of infill</p> <p>OR</p> <p>use of FRL –/120/120 rated Blocks/Bricks</p>	
Fire Dampers	<p>FRL –/120/– (Integrity)</p> <p>Bullock Model 4900 Curtain Fire Damper (6mm FC sheet around damper frame to PVC facing both sides</p> <p>OR</p> <p>ANY conventional curtain/blade fire damper tested or assessed for –/120/– to AS1530.4 in concrete walls 150mm thick</p>	
Note: Installation must be in accordance with manufacture's requirements, with variations as detailed in CSIRO assessment report FC3380		

Acoustic Performance

Acoustic performance requirements for a building project are determined by the NCC, local authorities and the developer requirements. A typical wall separating sole occupancy units is required to have an R_w+C_{tr} not less than 50 when measured in an acoustic laboratory.

Laboratory and Field Performance







There is however the verification clause that states that when the wall is installed in the actual dwelling that it shall achieve not less than a $D_{ntw}+C_{tr}$ of 45. In the end, it is the field conditions that dominate, as people do not live in acoustic laboratories. It is important that all the components in the chain of providing sound insulation have adequate performance and it is critically important to demonstrate in an acoustic laboratory that the chosen element has the potential performance.

Acoustic Performance

The acoustic performance of the rediwall® systems in various wall configurations have been assessed by Acoustic Logic Consultancy Pty Ltd.

The TABLE A10 provides acoustic performance ratings for unclad rediwall systems with PVC in place. These systems have been assessed by Acoustic Logic Consultancy Pty Ltd.

TABLE A10: Acoustic Performance Ratings for Standard Rediwall® Wall Systems (unclad with PVC in place)

Rediwall® System	Description		R _w	C _{tr}	R _w +C _{tr}
RW110C	110mm thick wall 105mm of concrete core		50	-5	45
RW156C	156mm thick wall/ 151mm of concrete core		54	-4	50
RW200C	200mm thick wall 195mm of concrete core Single or double reinforcement options		58	-5	53
RW256S	Double reinforcement, 251mm of concrete core		60	-5	55
RW275S	Double reinforcement, 270mm of concrete core		61	-5	55
RW300S	Double reinforcement, 295mm of concrete core		61	-5	55

Some typical rediwall® wall configurations and their assessed acoustic performance are given below. For further assistance on wall configurations and acoustic performance assessments, please contact AFS Technical Services.

TABLE A11: Sample Rediwall® Wall System Applications – Acoustic Performance Ratings

Rediwall®	Typical Application	Rediwall® System ¹	R _w	C _{tr}	R _w +C _{tr}
RW110C	External or dry to common area	afs rediwall® 110mm, 20mm air gap, 64mm Rondo Stud frame, Bradford Acoustigard insulation (75mm R1.8), 6mm Ceminseal Wallboard	62	-10	52
RW156C	External or dry to common area	afs rediwall® 156mm, 20mm air gap, 64mm Rondo Stud frame, Bradford Acoustigard insulation (75mm R1.8), 6mm Ceminseal Wallboard	65	-10	55
RW156C	Inter-tenancy dry to dry	13mm Gyprock Standard Plasterboard, 64mm Rondo Stud frame, Bradford or Martini non-rigid insulation (11kg/m ²), 20mm air gap, afs rediwall® 156mm, 13mm Gyprock Standard Plasterboard	65	-10	55
RW156C	Inter-tenancy wet to wet	6mm Ceminseal wallboard, 64mm Rondo Stud frame, Bradford or Martini non-rigid insulation (11kg/m ²), 20mm air gap, afs rediwall® 156mm, 20mm air gap, Bradford or Martini non-rigid insulation (11kg/m ²), 64mm Rondo Stud frame, 6mm Ceminseal wallboard	>70	-10	>60
RW156C	Inter-tenancy dry to service shaft	13mm Gyprock Standard Plasterboard, afs rediwall® 156mm, 20mm air gap, Bradford or Martini non-rigid insulation (11kg/m ²), 64mm Rondo Stud frame, 6mm Ceminseal wallboard	65	-10	55

¹ To achieve a discontinuous construction a separate stud wall is required. To maintain discontinuous construction the plumbing or other services must be run within the studs of the separating wall. There must be no direct connection between the plumbing services and the afs rediwall® wall other than at the perimeter.

Thermal Insulation

A primary objective for a designer when planning a building is to design a building fabric – external elements such as ceilings, roofs and floors, that will deliver a cost effective, comfortable living or working environment for the inhabitants.

AFS rediwall® walls being a monolithic concrete barrier possess inherent features which greatly assist the designer in achieving the objective of thermal mass and air tightness.

Energy Efficiency

The NCC contains thermal performance requirements in terms of **minimum Total R** for building fabric (the external ceilings, floors and walls) of new buildings in Australia.

The total R-Value is the total thermal resistance of a building surface, including indoor and outdoor air film resistance.

Thermal Insulation & Mass

The NCC recognises the benefit of thermal capacity or mass, and so provides R concessions for heavyweight walls such as afs rediwall® walls.

Heavy mass delays the transfer of outdoor temperature variations, improving indoor comfort. The concrete construction of afs rediwall® walls provides a significant thermal mass barrier to the external elements. If necessary additional insulation materials may be installed with afs rediwall® walls to achieve higher R-values specified by the BCA. This in turn not only enhances occupant comfort, but also reduces heating/cooling costs and may also improve the acoustic performance of the wall. Insulation materials should be installed with afs rediwall® walls so as to form a continuous thermal barrier.

Condensation Management

An afs rediwall® external wall system can comply to the NCC 2019 Amendment 1 F6.2(a). Pliable Building Membrane deemed to satisfy provisions where the rediwall® as the external wall can have a vapour permeable pliable building membrane (complaint to AS4200.1 and AS4200.2) installed by others to the inside face of the rediwall® prior to any insulation layer, then internal wall lining system. Refer to Volume 2 - Detailing & Finishing Guide wall system details.

Consideration should be taken for poor sealing and high-level open wall vents, water vapour from clothes dryers, showers and baths was carried from the building before condensing. With increased insulation and better techniques for preventing heat loss, make it more difficult for water vapour to exit the dwelling as there are no air gaps for the air to carry it away, so it condenses on the coolest surface, typically the window glass can be more prevalent, however, it is an 'operational' issue rather than a building fault.

Activities such as failing to run fans while showering and while a room dries out, drying clothes inside without a dryer and exhaust fan operating, and appliances such as food steamers, kettles, urns and humidifiers, all contribute to water vapour and therefore potentially to condensation. The formation of condensation typically illustrates that the building is well sealed against draughts and is well insulated.

Prevention of condensation can be achieved by the following common practices:-

- Running bathroom fans while showering and leaving them on for a time afterwards.
- Dry clothes outside, in a dryer with the laundry fan running or on a rack in the bathroom with the bathroom fan running, or in a communal drying facility.
- Avoid using humidifiers and other appliances which create steam/water vapour.
- If using steamers, urns or boiling water, ensure the rangehood is operating. (Rangehoods should exhaust to outside and must not be recycling type.)
- Leave windows ajar some of the time, particularly in bathrooms.
- Consider opening the outside doors and windows for a few minutes each day to 'flush out' humid air.

AFS Rediwall® Thermal Performance

AFS Rediwall® wall systems have been assessed for their thermal performance by thermal efficiency consultants, James M Fricker Pty Ltd (JMP). The thermal performance assessments in accordance with AS/NZS 4859.1 – 2018 for the rediwall® unclad walls with PVC in place are detailed in the following table.

Rediwall® System	Thermal Resistance
RW110C	R 0.091m ² K/W
RW156C	R 0.123m ² K/W
RW200C	R 0.153m ² K/W
RW256S	R 0.192m ² K/W
RW275S	R 0.205m ² K/W
RW300S	R 0.223m ² K/W

Total R-value thermal assessments have been performed for a variety of afs rediwall® wall configurations.

The following table provides examples of some afs rediwall wall system configurations along with their total R-values.

For assistance with additional rediwall® wall configurations and thermal performance assessments, please contact AFS Technical Services.

TABLE A12: Examples of AFS Rediwall® Wall System Configurations and Thermal Performance Total R-Values

AFS Rediwall®	Composition	System Overview	Total R- Value	
			Summer	Winter
RW156C	<ul style="list-style-type: none"> – RW156C – 28mm Rondo furring channel on Betafix Clip – Bradford 25mm Xtroliner R1.19 – 6mm Cemintel Wallboard 		1.61	1.75
RW156C	<ul style="list-style-type: none"> – RW156C – 28mm Rondo furring channel on Betafix Clip – Bradford 25mm Xtroliner R1.19 – 13mm Gyprock standard plasterboard 		1.67	1.81
RW156C	<ul style="list-style-type: none"> – RW156C – 20mm air gap – 64mm Rondo stud frame – Bradford Acoustigard 75mm R1.8 – 13mm Gyprock standard plasterboard 		2.24	2.44

Weatherproofing

For any external façade design applicable to a building, it is essential that the system adopted is capable of withstanding the various environmental conditions which the façade is subject to during its life. In particular the prevention of water ingress into the building is critical. afs rediwall® as an external façade, with an applied weatherproofing coating performs as a successful barrier to water ingress, and has been tried and proven on numerous buildings, many of which are in coastal locations. The system chiefly relies upon the following:

1. Adoption of horizontal slab junction details as recommended by AFS. Refer to Volume 2 for further details.
2. The water resistance of the PVC face used in afs rediwall® itself.
3. Appropriate location of flashings, especially to cap exposed parapet walls typically located on the top level of buildings.
3. Correct application of a quality external weatherproofing coating system to supplier's specifications.

AFS Rediwall® systems will comply with the weatherproofing performance verification methods FV1 Weatherproofing (Volume 1) and V.2.2.1 (Volume 2) of the National Construction Code, in accordance with the report "Weatherproofing to NCC 2016 afs rediwall® System, AECOM Dec 2017.

Termite Resistance

Australian Standard AS 3660.1 – Termite Management – New building works, Clause 4.3.2.2 confirms that as long as the construction joints at the wall/concrete slab junction are designed and constructed in accordance with AS2870 or AS3600, no other termite treatment is required as the junction becomes a suitable termite barrier.

Furthermore, rediwall®, consisting of concrete elements designed and constructed in accordance with AS3600 as a monolithic construction, together with PVC linings in accordance with AS3600.1, Clause 3.2, is deemed to be termite resistant.

Bushfire Resistance

AFS Rediwall® is suitable for use in external wall construction in designated bushfire prone areas. Rediwall® systems have been fire tested to confirm Fire Resistance Levels of 60/60/60 up to 240/240/240. Refer to the Fire Resistance Levels section of this guide.

Australian Standard AS3959 – Construction of buildings in bushfire prone areas, Clause 9.4, Item C, and CI 3.4 confirm that external wall systems with an FRL 30/30/30 or –/30/30 or higher are suitable for all Bushfire Attack Levels (BAL), i.e. BAL-Low to BAL-FZ.

NCC Vol. 1, Part C5 – Construction in Bushfire Prone Areas and Vol. 2, Part 3.7.4 confirms AS3959 as a deemed to satisfy solution and acceptable construction manual, respectively.

Appendices

The following are sample documents for:

AFS Rediwall® Standard Bracing & Lifting Bar

AFS Rediwall Standard Bracing Drawing and Certificate

AFS Rediwall® approved N16 Lifting Bar Drawing and Certification

Certifications

Rediwall® Codemark Certification

CM30107

Fire Resistance Level (FRL)

AS1530.4 FRL Fire Test Certificates

AS1530.4 FRL Assessment Report

AS1530.4 FRL Service Penetration Test and Assessment Report

Non-combustibility and Fire Performance

Stephen Grubits & Associates Safety Engineers, Rediwall® – Non-Combustibility Assessment Report

AS5113 Facade Fire Test Report

AS5637.1 Classification (AS/ISO 9705 Room Test) Report

AS1530.3 Fire Hazard Properties Fire Test Certificates

Acoustic Performance

Acoustic Logic Consultancy – Acoustic Performance Certificates for – RW110C, RW156C, RW200C, RW256S & RW300S.

Thermal Performance

James M Fricker Pty Ltd – R-value certificates – RW110C, RW156C, RW200C, RW256S, RW275S and RW300S.

Weatherproofing

AECOM Weatherproofing Verification Report.

AFS Rediwall Standard Bracing


NOTES:

1. ENSURE CORRECT ANCHORS & F/WNC USED AS PER THE TABLE FOR MAXIMUM WALL HEIGHT, FLOORING & PARTITION.
2. REFER AS INSTALLATION MANUAL FOR INSTALLATION GUIDELINES. BRACES TO REMAIN IN PLACE UNTIL TOP OF WALL STABILISED BY STRUCTURE OR AS INSTRUCTED BY ENGINEER.
3. INSTALLATION CONTRACTOR TO REVIEW FOR SUITABILITY OF BRACING SYSTEM.
4. BRACES TO BE INSPECTED ON RETURN FOR DAMAGE, STRAIGHTNESS & PLAY IN FITTINGS. ANY DEFECTIVE BRACES TO HAVE TAGGING REMOVED & BRACE DISCARDED OR REPAIRED.
5. BASED ON MAXIMUM BRACE INSTALLATION PERIOD OF 4 DAYS FOR BRACING PANELS.
6. BRACING PANELS TO BE REMOVED AFTER INSTALLATION OF FORMING PRIOR TO CONCRETE POUR.
7. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH S02 & S03

Type	Minimum Design Capacity, kN
Primary fixing - 12g Timber Screws into PVC joint	1.24
Secondary fixing - 12g Timber Screw into Single PVC Face	0.73


Brace	40x1.6 SHS C350 Standard Brace
Maximum Length (pin-pin)	2800
Spacing	1100

Region	Non Cyclonic A1-A7
Terrain Category	TC3
V.100yr	41 m/s





REDIWALL PANEL

Maximum Height Floor AGL(Z)	
Bottom Anchor Alternatives	< 20m
Hilti HUS-H Hilti HUS-H Hilti HUS-H	Maximum Temporary Wall height, mm
10x65	10x90 14x80
1	1 1 1
1	1 1 1
1	1 1 1
	3300 3000 2500




REDIWALL BRACE ARRANGEMENT
(MAX. WALL HEIGHT OF 3300mm)

ISSUE	NOTES ISSUED FOR CONSTRUCTION	DATE 10/27/99	SCALE: 1"
A			11
			12
			13
			14
			15
			16
			17
			18
			19
			20
			21
			22
			23
			24
			25
			26
			27
			28
			29
			30
			31
			32
			33
			34
			35
			36
			37
			38
			39
			40
			41
			42
			43
			44
			45
			46
			47
			48
			49
			50
			51
			52
			53
			54
			55
			56
			57
			58
			59
			60
			61
			62
			63
			64
			65
			66
			67
			68
			69
			70
			71
			72
			73
			74
			75
			76
			77
			78
			79
			80
			81
			82
			83
			84
			85
			86
			87
			88
			89
			90
			91
			92
			93
			94
			95
			96
			97
			98
			99
			100

 Lvl 2, 19 Harris Street Pymont, NSW 2009 T 02 9817 2811 E info@mydconsulting.com				PROJECT		ORDER REF P7351	
DATE 13/02/2019		DRAWN NY		CHECKED AM		DATE 13/02/19	
DRAWING TITLE REDWALL BRACE ARRANGEMENT OPTION 1		SCALE AS SHOWN		SHEET NUMBER S-1011(0-3)		SHEET 1	

DO NOT SCALE OFF DRAWINGS
DUE TO LIMITS OF PRINTING EQUIPMENT
REQUIRED DIMENSIONS TO BE USED, ALL DIMENSIONS TO BE CHECKED ON SITE

AFS Rediwall® Standard Lifting Bar



Rediwall® CodeMark Certificate of Conformity

Certificate of Conformity



Global-Mark Pty Ltd,
Suite 4.07, 32 Delhi
Road, North Ryde
NSW 2113, Australia

Tel: +61 (0)2 9886
0222 - www.Global-Mark.com.au

Certificate Holder:

AFS Systems Pty Ltd
110 Airis Road
Minto, NSW, 2566
Tel: 1300 727 237
afsformwork.com.au

Certificate number: CM 30107

THIS TO CERTIFY THAT

AFS REDIWALL®

Type and/or use of product:

AFS REDIWALL® is a permanent formwork system for load-bearing reinforced concrete walls designed by a Professional Engineer in accordance with AFS Rediwall Volume 1 Design, Performance & Compliance Guide April 2019 Edition and AS 3600:2009 (Incorporating Amendment No.1 and Amendment No.2).

Description of product:

AFS REDIWALL® comprises:

1. Interlocking PVC extrusions as permanent formwork.
2. PVC tracks, corners, joiners and associated accessories.
3. Fibre cement sheet end closures.
4. Reinforcing steel.
5. Concrete fill.

AFS REDIWALL® types are as follows, the numerical values representing the thickness of the wall in millimetres:

1. RW110C Single Reinforcement.
2. RW156C Single Reinforcement.
3. RW200C Single Reinforcement.
4. RW200C Double Reinforcement.
5. RW256S Double Reinforcement.

Scope of certification: The CodeMark Scheme is a building product certification scheme. The rules of the Scheme are available at the ABCB website www.abcb.gov.au. This Certificate of Conformity is to confirm that the relevant requirements of the Building Code of Australia (BCA) as claimed against have been met. The responsibility for the product performance and its fitness for the intended use remain with the certificate holder. The certification is not transferable to a manufacturer not listed on Appendix A of this certificate.

Disclaimer: The Scheme Owner, Scheme Administrator and Scheme Accreditation Body do not make any representations, warranties or guarantees, and accept no legal liability whatsoever arising from or connected to, the accuracy, reliability, currency or completeness of any material contained within this certificate; and the Scheme Owner, Scheme Administrator and Scheme Accreditation Body disclaim to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this certificate.

The purpose of Global-Mark construction site audits is to confirm the practicability of installing the product; and to confirm the appropriateness and accuracy of installation instructions. In placing the CodeMark mark on the product/system, the certificate holder makes a declaration of compliance with the certification standard(s) and confirms that the product is identical to the product certified herein. In issuing this Certificate of Approval Global-Mark has relied on the expertise of external bodies (laboratories, and technical experts).

Herve Michoux

Herve Michoux
Global-Mark Managing Director

P. Gardner

Peter Gardner
Unrestricted Building Certifier



Certificate number: CM30107

This certificate is only valid when reproduced in its entirety.

Page 1 of 10

AFS Rediwall® Fire Resistance Level (FRL) Reports

INFRASTRUCTURE TECHNOLOGIES

www.csiro.au

14 Julius Avenue, North Ryde NSW 2113
 PO Box 310, North Ryde NSW 1670, Australia
 T (02) 9490 5444 • ABN 41 687 119 230



Certificate of Test

No. 2667

"Copyright CSIRO 2015 ©"

Copying or alteration of this report
 without written authorisation from CSIRO is forbidden.

This is to certify that the element of construction described below was tested by the CSIRO Infrastructure Technologies in accordance with Australian Standard 1530, Methods for fire tests on building materials, components and structures, Part 4-2005 on behalf of:

AFS Products Group Pty Ltd
 22-24 Somerville Circuit
 Emu Plains NSW

A full description of the test specimen and the complete test results are detailed in the Division's Sponsored Investigation report numbered FS/ 1704.

Product Name: Load-bearing 150-mm thick AFS 150 Rediwall Panel structural wall system.

Description: The specimen comprised a reinforced concrete wall system 3000-mm high x 3000-mm wide x 150-mm thick made up of twelve pre-fabricated permanent formwork panels core-filled with concrete after assembly. The pre-fabricated permanent formwork system comprised 250-mm wide x 3000-mm high x 150-mm thick AFS 150 Rediwall panels. The extruded PVC panels comprised 2.5-mm thick perforated internal webs spaced at nominally 80-mm centres, as shown in drawing numbered AFS-DT-345, dated 8 April 2015, by AFS Systems Pty Ltd. The panels interconnected vertically by integrated sliding male to female connectors to form a hollow panel wall. The ends of the wall were finished with solid End Caps, while the bottom consisted of a perforated Floor Track. The wall was reinforced with N12 reinforcing bars at 350-mm centres vertically and 400-mm centres horizontally. The panels were appropriately braced and 32 Mpa, 120-mm slump concrete mix was pumped in through the top openings and trowelled off along the top, when completely filled. A total load of 700 kN was applied to the specimen for the duration of the test. The load requested by the client, was applied uniformly along the top of the wall.

The element of construction described above satisfied the following criteria for fire-resistance for the period stated.

Structural Adequacy	no failure at 241 minutes
Integrity	no failure at 241 minutes
Insulation	no failure at 241 minutes

and therefore for the purpose of Building Regulations in Australia, achieved a fire-resistance level (FRL) of 240/240/240. The FRL is applicable for exposure to fire from either direction.

This certificate is provided for general information only and does not comply with regulatory requirements for evidence of compliance.

Testing Officer: Chris Wojcik

Date of Test: 17 July 2015

Issued on the 7th day of August 2015 without alterations or additions.

B. Roddy

Brett Roddy
 Manager, Fire Testing and Assessments



NATA Accredited Laboratory
 Number: 165
 Corporate Site No 3625
 Accredited for compliance with ISO/IEC 17025

INFRASTRUCTURE TECHNOLOGIES

www.csiro.au

14 Julius Avenue, North Ryde NSW 2113
 PO Box 310, North Ryde NSW 1670, Australia
 T (02) 9490 5444 • ABN 41 687 119 230



Certificate of Test

No. 2580

"Copyright CSIRO 2014 ©"

Copying or alteration of this report
 without written authorisation from CSIRO is forbidden.

This is to certify that the element of construction described below was tested by the CSIRO Division of Materials Science and Engineering in accordance with Australian Standard 1530, Methods for fire tests on building materials, components and structures, Part 4-2005 on behalf of:

AFS Products Group Pty Ltd
 22-24 Sommerville Circuit
 Emu Plains NSW

A full description of the test specimen and the complete test results are detailed in the Division's Sponsored Investigation report numbered FSV 1654.

Product Name: 200-mm thick, load-bearing AFS 250 Rediwall Panel, structural wall system.

Description: The specimen comprised a reinforced concrete wall system 3000-mm high x 3000-mm wide x 200-mm thick made up of twelve pre-fabricated permanent formwork panels core-filled with concrete after assembly. The pre-fabricated permanent formwork system comprised 250-mm wide x 3000-mm high x 200-mm thick AFS 250 Rediwall panels. The extruded PVC panels comprised 2.5-mm thick perforated internal webs spaced at nominally 80-mm centres, as shown in drawing titled "AFS U250 Panel 200 THK Rediwall", dated 22 July 2014, by LMGDS Pty Ltd. The panels interconnected vertically by integrated sliding male to female connectors to form a hollow panel wall. The ends of the wall were finished with solid End Caps, while the bottom consisted of a perforated Floor Track. The wall was reinforced with N12 reinforcing bars at 350-mm centres vertically and 400-mm centres horizontally. The panels were appropriately braced and 32 Mpa, 120-mm slump concrete mix was pumped in through the top openings and trowelled off along the top, when completely filled. The concrete mix design is specified in Hanson Construction Materials Pty Ltd report in Appendix D. A total load of 1000 kN was applied to the specimen for the duration of the test. The wall specimen wall was constructed on 20 January 2014.

The element of construction described above satisfied the following criteria for fire-resistance for the period stated.

Structural Adequacy	no failure at 241 minutes
Integrity	no failure at 241 minutes
Insulation	no failure at 241 minutes

and therefore for the purpose of Building Regulations in Australia, achieved a fire-resistance level (FRL) of 240/240/240. The FRL is applicable for exposure to fire from either direction.

This certificate is provided for general information only and does not comply with regulatory requirements for evidence of compliance.

Testing Officer: Chris Wojcik Date of Test: 11 August 2014

Issued on the 5th day of September 2014 without alterations or additions.

Brett Roddy
 Manager, Fire Testing and Assessments



This document is issued in accordance with NATA's accreditation requirements.
 Accreditation No. 165 – Corporate Site No. 3625
 Accredited for compliance with ISO/IEC 17025

Exova Warringtonfire Aus Pty Ltd
Unit 2, 409-411 Hammond Road
Dandenong Victoria 3175
Australia
T: +61 (0)3 9767 1000
F: +61 (0)3 9767 1001
W: www.exova.com



Testing. Advising. Assuring.

EWFA CERTIFICATE OF ASSESSMENT

CERTIFICATE No : SFC 51713600.1

Page 1 of 2

Report Sponsor	Certificate Issue Date	Products Name
AFS Systems Pty Ltd 110 Airds Road Minto NSW 2566	17/04/2018	The fire resistance performance of AFS Rediwall loadbearing wall systems if tested in accordance with AS1530.4-2014

Assessment Report Reference	Referenced Standard	Report Issue Date	Report Validity Date
EWFA 51713600.1	AS1530.4-2014	17/04/2018	30/04/2023

Introduction

The element of construction described below was assessed by this laboratory on behalf of the report sponsor in accordance with the stated test standard and achieved the results stated below. Refer to the referenced test report for a complete description of the assessed construction.

Assessed systems description and performance

Based on the discussion presented in the assessment report, it is the opinion of this testing authority that if the specimen described in section 1 of the report had been modified within the scope of section 3, it will achieve the performance as stated below if tested in accordance with the test method referenced in Section 4 and subject to the requirements of Section 7:

RW156C Wall System, FRL: 240/240/240, uniformly applied load is 700kN

RW200C Wall System, FRL: 240/240/240, uniformly applied load is 1000kN

RW256S Wall System, FRL: 240/240/240, uniformly applied load is 1000kN

For full and detailed description of the assessed systems please refer to assessment report EWFA 51713600.1

Conditions/Validity

- THIS CERTIFICATE IS PROVIDED FOR GENERAL INFORMATION ONLY AND DOES NOT COMPLY WITH THE REGULATORY REQUIREMENTS FOR EVIDENCE OF COMPLIANCE.
- Reference should be made to the relevant test report or regulatory information report to determine the applicability of the test result to a proposed installation. Full details of the constructions and justification for the conclusions given, along with the validity statements, are given in the assessment reports.
- The assessment report or short form assessment report does not provide an endorsement by Exova Warringtonfire Aus Pty Ltd of the performance of the actual products supplied. It is intended to provide a brief outline of the above referenced assessment reports and not to replace them.
- The conclusions in this certificate of assessment relate to the configurations as detailed, and should not be applied to any other configuration. The conclusions expressed in this document assess fire hazard, but it should be recognised that a single test method will not provide a full assessment of fire hazard under all conditions.
- Full copies of the assessment and relevant test reports may be obtained from the sponsor.



STEPHEN GRUBITS & ASSOCIATES

Stephen Grubits & Associates Pty Ltd
Suite 5A, Level 4, 189 Kent Street, Sydney NSW 2000
PO Box N522, Grosvenor Place NSW 1220
Tel: +61 2 9247 1444 Fax: +61 2 9247 1499
Email: sydney@grubits.com.au
ABN: 24 075 049 688

File: 2013/277.65 R2.2 **ASSESSMENT SUMMARY**

Product Name	CSR Rediwall®
Manufacturer	AFS Walling Solutions, a division of CSR Ltd
Assessment Reports	Stephen Grubits & Associates, Fire Engineering Report 2013/277.65 R1.4, Issued 01 July 2020
Applicable Building Code	National Construction Code 2019 Amendment 1 Building Code of Australia (BCA), Volume One
Relevant BCA Performance Requirements	CP1 and CP2
Purpose of this document	To summarise findings of SGA Report Number 2013/277.65 R1.4
Date of Issue:	01/07/2020
Date of Expiry	Date NCC 2019 Amendment 1 is amended or superseded

Overview

The fire-resisting performance of the above-mentioned product was assessed by Stephen Grubits & Associates (SGA) at the request of AFS Walling Solutions, a division of CSR Ltd. The fire-resistance level achieved by 110 mm thick CSR Rediwall® walls was evaluated based on test data relating to 150 mm thick and 200 mm thick CSR Rediwall® (see limitations). The findings were applicable to 110 mm thick CSR Rediwall® of the following dimensions

- 2.7 m floor-to-floor wall height, restrained such that the k factor (in accordance with AS 3600-2018) is no greater than 0.75.
- 2.9 m floor-to-floor wall height, restrained such that the k factor is no greater than 0.75.
- 2.2 m floor-to-floor wall height, restrained such that the k factor is no greater than 1.

Assumptions and Limitations

The assessment is strictly limited to 110 mm thick CSR Rediwall® with the following characteristics:

- One layer of N12 steel reinforcing bars located in the centre of the wall thickness at 350 mm centres vertically and 400 mm centres horizontally
- Rediwall® to be arranged such that its plastic webs are in a vertical arrangement only.
- The FRLs described in this document are valid for exposure to fire on one-side only.

Issued by:	Carlos Quaglia (C10 - BPB0334)		Approved by:	Rose Pengilly (Director)	
------------	-----------------------------------	---	--------------	-----------------------------	---

Fire-resistance test on services penetrating vertical separating elements

Test Report

Author: Chris Wojcik
Report number: FSV 2094
Date: 21 May 2020
Client: AFS Systems Pty Ltd

Commercial-in-confidence



NATA Accredited Laboratory
Number: 165
Corporate Site No 3625
Accredited for compliance with ISO/IEC 17025 - Testing

INFRASTRUCTURE TECHNOLOGIES
www.csiro.au



The fire resistance of AFS Rediwall and AFS Logicwall including various service penetrations in accordance with AS 1530.4 – 2014 and AS 4072.1 – 2005 Amdt 1

Assessment Report

Author: Keith Nicholls

Assessment Number: FCO-3380 Rev B

Quote Number: C05209

Date: 8th July 2020

The Client: AFS Systems Pty Ltd

Commercial-in-confidence

Stephen Grubits & Associates – Rediwall® CodeMark Evaluation



STEPHEN GRUBITS & ASSOCIATES

Stephen Grubits & Associates Pty Ltd
 ABN 24 075 049 688
 PO Box N522, Grosvenor Place NSW 1220
 T: +61 2 9247 1444 E: sydney@grubits.com.au W: www.grubits.com.au


Rediwall® CodeMark Certification

FOR CODEMARK EVALUATION

REPORT 2013/277.78 R1.5

• FIRE SAFETY ENGINEERS •

Rediwall® AS5113 Facade Test Report



EXOVd
Warringtonfire



TEST REPORT

External Wall reaction to fire testing of a
110mm thick external wall system in
accordance with AS5113: 2016.

EWFA Report No:

51713900.1

Report Sponsor:

AFS Systems Pty Ltd
110 Airds Road
Minto NSW 2566

Test Date:

17 October 2017

Testing, Calibrating, Advising

Rediwall® AS5637.1 Classification Report

warringtonfire
Proud to be part of  element



Classification report

Classification of wall and ceiling lining in accordance with
AS 5637.1:2015

Test sponsor: AFS Systems Pty Ltd

Product: Concrete-filled AFS rediwall, PVC reference No: RE05D02DB

Report number: ASCRRTF190226

Test date: 25 November 2019 Revision: R2.0

Rediwall® AS1530.3 Fire Hazard Properties Test Report

AWTA PRODUCT TESTING

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing

A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031

P.O Box 240, North Melbourne, Victoria 3051

Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

Client : CSR - AFS Walling Solutions
110 Airs Road
Minto NSW 2566

Test Number : 17-003237
Issue Date : 21/06/2017
Print Date : 28/06/2017

Sample Description Clients Ref : "Rediwall"
Walling system with PVC facing
Nominal Composition : PVC/Concrete
Nominal Mass per Unit Area/Density : Approx. 450kg/m2
Nominal Thickness : Approx. 60mm

AS/NZS 1530.3-1999

Methods for Fire Tests on Building Materials, Components and Structures
Part 3: Simultaneous Determination of Ignitability,
Flame Propagation, Heat Release and Smoke Release

Face tested:	Face	
Date tested:	21/06/2017	
	Standard Error	Mean
Ignition time	0.43	10.35 min
Flame propagation time	Nil	Nil sec
Heat release integral	2.2	16.8 kJ/m²
Smoke release, log d	0.0400	-0.4439
Optical density, d		0.3670 / metre
Number of specimens ignited:		6
Number of specimens tested:		6
Regulatory Indices:		
Ignitability Index		10 Range 0-20
Spread of Flame Index		0 Range 0-10
Heat Evolved Index		0 Range 0-10
Smoke Developed Index		6 Range 0-10

96083

20342

Page 1 of 2

© Australian Wool testing Authority Ltd
Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025
- Chemical Testing
- Mechanical Testing
- Performance & Approvals Testing

: Accreditation No. 983
: Accreditation No. 985
: Accreditation No. 1356



Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

APPROVED SIGNATORY

MICHAEL A. JACKSON B.Sc.(Hons)
MANAGING DIRECTOR

0204/11/06



DIRECTORS
MATTHEW PALAVIDIS
VICTOR FATTORETTO
MATTHEW SHIELDS

20181292.1/1801A/R2/JL

18/01/2019

CSR - AFS Walling Solutions
110 Airs Road
MINTO NSW 2566

AFS Rediwall 110mm Base Wall - Acoustic Performance Opinion - AFS6001

This letter presents the professional acoustic assessment of Acoustic Logic Consultancy (ALC) in relation to the following AFS wall system:

- AFS Rediwall 110mm Base Wall

R_w : Weighted Sound Reduction Index which is calculated using the third octave frequency bands between and including 100 Hz to 3150 Hz.

D_{nTw} : Weighted Standardised Level Difference which is calculated using the third octave frequency bands between and including 100 Hz to 3150 Hz.

C_{tr} : Spectrum adaptation term.

It is the opinion of ALC that this construction will achieve the acoustic rating presented in the table below:

Table 1 – Predicted Acoustic Rating

Predicted R_w	Predicted C_{tr}	Predicted $R_w + C_{tr}$
50	-5	45

SYDNEY
A: 9 Sarah St
MASCOT 2020
T: (02) 8339 8000

SYDNEY MELBOURNE BRISBANE CANBERRA
LONDON DUBAI SINGAPORE GREECE

ABN: 11 068 954 343

The information in this document is the property of Acoustic Logic Consultancy Pty Ltd ABN 11 068 954 343 and shall be returned on demand. It is issued on the condition that, except with our written permission, it must not be reproduced, copied or communicated to any other party nor be used for any purpose other than that stated in particular enquiry, order or contract with which it is issued.

I:\Jobs\2018\20181292\20181292.1\20190118JLA_R2_Acoustic Performance Opinion - AFS6001.docx



DIRECTORS
MATTHEW PALAVIDIS
VICTOR FATTORETTO
MATTHEW SHIELDS

20181292.1/1801A/R0/JL

18/01/2019

CSR - AFS Walling Solutions
110 Airs Road
MINTO NSW 2566

AFS Rediwall 156mm Base Wall - Acoustic Performance Opinion - AFS7001

This letter presents the professional acoustic assessment of Acoustic Logic Consultancy (ALC) in relation to the following AFS wall system:

- AFS Rediwall 156mm Base Wall

R_w : Weighted Sound Reduction Index which is calculated using the third octave frequency bands between and including 100 Hz to 3150 Hz.

D_{nTw} : Weighted Standardised Level Difference which is calculated using the third octave frequency bands between and including 100 Hz to 3150 Hz.

C_{tr} : Spectrum adaptation term.

It is the opinion of ALC that this construction will achieve the acoustic rating presented in the table below:

Table 1 – Predicted Acoustic Rating

Predicted R_w	Predicted C_{tr}	Predicted $R_w + C_{tr}$
54	-4	50

SYDNEY
A: 9 Sarah St
MASCOT 2020
T: (02) 8339 8000

SYDNEY MELBOURNE BRISBANE CANBERRA
LONDON DUBAI SINGAPORE GREECE

ABN: 11 068 954 343

The information in this document is the property of Acoustic Logic Consultancy Pty Ltd ABN 11 068 954 343 and shall be returned on demand. It is issued on the condition that, except with our written permission, it must not be reproduced, copied or communicated to any other party nor be used for any purpose other than that stated in particular enquiry, order or contract with which it is issued.

I:\Jobs\2018\20181292\20181292.1\20190118JLA_R0_Acoustic Performance Opinion - AFS7001.docx



DIRECTORS
MATTHEW PALAVIDIS
VICTOR FATTORETTO
MATTHEW SHIELDS

20181292.1/1801A/R0/JL

18/01/2019

CSR - AFS Walling Solutions
110 Airs Road
MINTO NSW 2566

AFS Rediwall 200mm Base Wall - Acoustic Performance Opinion - AFS8001

This letter presents the professional acoustic assessment of Acoustic Logic Consultancy (ALC) in relation to the following AFS wall system:

- AFS Rediwall 200mm Base Wall

R_w : Weighted Sound Reduction Index which is calculated using the third octave frequency bands between and including 100 Hz to 3150 Hz.

D_{nTw} : Weighted Standardised Level Difference which is calculated using the third octave frequency bands between and including 100 Hz to 3150 Hz.

C_{tr} : Spectrum adaptation term.

It is the opinion of ALC that this construction will achieve the acoustic rating presented in the table below:

Table 1 – Predicted Acoustic Rating

Predicted R_w	Predicted C_{tr}	Predicted $R_w + C_{tr}$
58	-5	53

SYDNEY
A: 9 Sarah St
MASCOT 2020
T: (02) 8339 8000

SYDNEY MELBOURNE BRISBANE CANBERRA
LONDON DUBAI SINGAPORE GREECE

ABN: 11 068 954 343

The information in this document is the property of Acoustic Logic Consultancy Pty Ltd ABN 11 068 954 343 and shall be returned on demand. It is issued on the condition that, except with our written permission, it must not be reproduced, copied or communicated to any other party nor be used for any purpose other than that stated in particular enquiry, order or contract with which it is issued.

I:\Jobs\20181292\20181292.1\20190118JLA_R0_Acoustic Performance Opinion - AFS8001.docx



**ACOUSTIC
LOGIC**

DIRECTORS

MATTHEW PALAVIDIS
VICTOR FATTORETTO
MATTHEW SHIELDS

20181292.1/1801A/R0/JL

18/01/2019

CSR - AFS Walling Solutions
110 Airs Road
MINTO NSW 2566

AFS Rediwall 256mm Base Wall - Acoustic Performance Opinion - AFS9001

This letter presents the professional acoustic assessment of Acoustic Logic Consultancy (ALC) in relation to the following AFS wall system:

- AFS Rediwall 256mm Base Wall

R_w : Weighted Sound Reduction Index which is calculated using the third octave frequency bands between and including 100 Hz to 3150 Hz.

D_{nTw} : Weighted Standardised Level Difference which is calculated using the third octave frequency bands between and including 100 Hz to 3150 Hz.

C_{tr} : Spectrum adaptation term.

It is the opinion of ALC that this construction will achieve the acoustic rating presented in the table below:

Table 1 – Predicted Acoustic Rating

Predicted R_w	Predicted C_{tr}	Predicted $R_w + C_{tr}$
60	-5	55

SYDNEY
A: 9 Sarah St
MASCOT 2020
T: (02) 8339 8000

SYDNEY MELBOURNE BRISBANE CANBERRA
LONDON DUBAI SINGAPORE GREECE

ABN: 11 068 954 343

The information in this document is the property of Acoustic Logic Consultancy Pty Ltd ABN 11 068 954 343 and shall be returned on demand. It is issued on the condition that, except with our written permission, it must not be reproduced, copied or communicated to any other party nor be used for any purpose other than that stated in particular enquiry, order or contract with which it is issued.

I:\Jobs\20181292\20181292.1\20190118JLA_R0_Acoustic Performance Opinion - AFS9001.docx



**ACOUSTIC
LOGIC**

DIRECTORS

MATTHEW PALAVIDIS
VICTOR FATTORETTO
MATTHEW SHIELDS

20181292.5/2004A/R1/GW

20/04/2020

CSR - AFS Walling Solutions
110 Airs Road
MINTO NSW 2566

275MM THICK AFS REDIWALL - ACOUSTIC ASSESSMENT

This letter presents the professional acoustic assessment of Acoustic Logic Consultancy (ALC) in relation to the following AFS wall system:

- AFS Rediwall 275mm Base Wall

R_w : Weighted Sound Reduction Index which is calculated using the third octave frequency bands between and including 100 Hz to 3150 Hz.

D_{nTw} : Weighted Standardised Level Difference which is calculated using the third octave frequency bands between and including 100 Hz to 3150 Hz.

C_{tr} : Spectrum adaptation term.

It is the opinion of ALC that this construction will achieve the acoustic rating presented in the table below:

Table 1 – Predicted Acoustic Rating

Wall	Predicted R_w	Predicted C_{tr}	Predicted $R_w + C_{tr}$
AFS 275mm Rediwall	61	-5	56

SYDNEY

A: 9 Sarah St

MASCOT 2020

T: (02) 8339 8000

SYDNEY MELBOURNE BRISBANE CANBERRA

LONDON DUBAI SINGAPORE GREECE

ABN: 11 068 954 343

The information in this document is the property of Acoustic Logic Consultancy Pty Ltd ABN 11 068 954 343 and shall be returned on demand. It is issued on the condition that, except with our written permission, it must not be reproduced, copied or communicated to any other party nor be used for any purpose other than that stated in particular enquiry, order or contract with which it is issued.

I:\Jobs\2018\20181292\20181292.5\20200420GWA_R1_Acoustic Assessment.docx



**ACOUSTIC
LOGIC**

DIRECTORS

MATTHEW PALAVIDIS
VICTOR FATTORETTO
MATTHEW SHIELDS

20181292.5/2004A/R2/GW

20/04/2020

CSR - AFS Walling Solutions
110 Airs Road
MINTO NSW 2566

300MM THICK AFS REDIWALL - ACOUSTIC ASSESSMENT

This letter presents the professional acoustic assessment of Acoustic Logic Consultancy (ALC) in relation to the following AFS wall system:

- AFS Rediwall 300mm Base Wall

R_w : Weighted Sound Reduction Index which is calculated using the third octave frequency bands between and including 100 Hz to 3150 Hz.

D_{nTw} : Weighted Standardised Level Difference which is calculated using the third octave frequency bands between and including 100 Hz to 3150 Hz.

C_{tr} : Spectrum adaptation term.

It is the opinion of ALC that this construction will achieve the acoustic rating presented in the table below:

Table 1 – Predicted Acoustic Rating

Wall	Predicted R_w	Predicted C_{tr}	Predicted $R_w + C_{tr}$
AFS 300mm Rediwall	61	-5	56

SYDNEY
A: 9 Sarah St
MASCOT 2020
T: (02) 8339 8000

SYDNEY MELBOURNE BRISBANE CANBERRA
LONDON DUBAI SINGAPORE GREECE

ABN: 11 068 954 343

The information in this document is the property of Acoustic Logic Consultancy Pty Ltd ABN 11 068 954 343 and shall be returned on demand. It is issued on the condition that, except with our written permission, it must not be reproduced, copied or communicated to any other party nor be used for any purpose other than that stated in particular enquiry, order or contract with which it is issued.

I:\Jobs\2018\20181292\20181292.5\20200420GWA_R2_Acoustic Assessment.docx

OVERALL “TOTAL R” (THERMALLY BRIDGED) THERMAL PERFORMANCE CALCULATIONS TO AS/NZS 4859 Parts 1 & 2:2018

The following calculations by James M Fricker Pty Ltd are based upon:

- a) AS/NZS 4859.1:2018 “Thermal insulation materials for buildings. Part 1: General criteria and technical provisions”,
- b) AS/NZS 4859.2:2018 “Thermal insulation materials for buildings. Part 2: Design”,
- c) the Australian Institute of Refrigeration Air-conditioning & Heating (AIRAH) Handbook (Edition 5, 2013), and (if necessary) the ASHRAE Fundamentals Handbook.

Initial results report Total R for each thermal path. These results are combined by area weighting and isothermal planes method to deduce **Overall Surface Total R**. This is per AS/NZS 4859.2:2018 Clause 4.3 – “A total resistance associated with a construction of materials, computed or measured over an area sufficient to be fully representative of the element of construction, and specified as a Total R-value, including surface film resistances and thermal bridging.”

Total R-values are based on product in-service conditions in accordance with AS/NZS 4859.2:2018 including the alteration of insulation Material R for temperature, and Air Space R for temperature and infrared emittance.


Each calculation result is subject to any specific notes and assumptions listed on the calculation.

If a construction differs from the described system, the thermal resistance may be different.

All calculations were done by James M Fricker, F.AIRAH F.IEAust CPEng NER APEC Engineer IntPE(Aus)



**ENGINEERS
AUSTRALIA**
Chartered Professional Engineer
MEMBER 1179647



JAMES M FRICKER PTY LTD
54 Felix Crescent
Ringwood North VIC 3134 Australia
Mobile: 0414 804 097
Phone: (03) 9879 5744
fricker@optusnet.com.au
http://fricker.net.au


Rediwall® Weatherproofing Assessment Report

AECOM Imagine it.
Delivered.

Weatherproofing Verification to NCC 2019 **Commercial-in-Confidence**
CSR Building Products Limited
13-May-2019

AFS Rediwall System


National Construction Code (NCC 2019)



NOTES:

A large rectangular area filled with a grid of small, evenly spaced dotted lines, intended for handwritten notes.

NOTES:

A large rectangular area filled with a grid of small, evenly spaced dotted lines, intended for handwritten notes.

PVC-based permanent formwork for basements, columns, blade
& party walls, lift & stair cores, retaining walls and retention tanks



Disclaimer: Information presented in this document is supplied in good faith and to the best of our knowledge was accurate at the time of preparation. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this

information in relation to their particular purpose or specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by AFS or CSR, or its staff for any loss or damage caused by any person acting or refraining from action as a result of misuse of this information.

(C) 2021 AFS Systems Pty Ltd ABN 455 760 727 88
BMS1827 0321 – MAR21

afs

afsformwork.com.au • 1300 727 237

AFS Systems Pty Ltd • 110 Airds Road, Minto NSW 2566

CSR